A19



Electrical						
Watt	9.5					
Power Factor	> 0.8					
Voltage	120 volt					
Frequency	60Hz					
Base Type	E26 Medium					
Operating Temperature Range	-4F to 104F					
Light						
Initial Lumens	820					
Lumens per Watt	86.3					
Color Temperature	5000K					
Color Rendering (CRI)	82					
Agency Approvals						
UL	Yes					
Energy Star	15,000 hours					
RoHS	Yes					
FCC	Yes					
Product Details						
Warranty	5 years 6 hr/day					
Diameter	2.36"					
Nominal Length	4.26"					
Rated Life	15,000 hours					

820 Lumen 9.5 Watt 5000K A19 Omni LED



PRODUCT DESCRIPTION


9.5 watt A19 Omni-directional EarthBulb LED provides 820 lumens and replaces 60 watt incandescent directional bulbs for over 80% energy savings. 5000K color of light is standard. Great for use in table lamps, floor lamps, wall sconce, and task lighting applications. Multi-Chipset LED and an advanced cooling system provides for 15,000 hours of LED life. Medium screw base. Energy Star rated product. Suitable for outdoor use, damp location, when installed in fixtures and not directly exposed to weather. Energy Star rated to be used in enclosed fixtures.

PRODUCT FEATURES

- This A bulb is Energy Star rated and provides 820 lumens, capable of dimming to less than 8%
- Omni directional beam angle provides full radial illumination
- Chipset provides 5000K daylight with a high color rendering rating of 82
- New heat sync system provides improved aesthetics and performance
- May be used in enclosed fixtures
- Suitable for damp locations





LUMINOUS DISTRIBUTION INTENSITY DIAGRAM



AVERAGE BEAM ANGLE (50%):225.3° Note: IES files available upon request.

MODEL NUMBER: LA19950DEF





Order Code	Pack Size	Individual UPC	Inner Pack UPC	Qty	Master Park UPC	Qty	
11052	1	840791110522	00840791110522	12	84079111052200	48	
Dimensions (inches - Length x Width x Height)							
11052	1	2.44 x 2.44 x 4.72	10.47 x 7.91 x 5.39	12	21.73 x 16.61 x 6.73	48	
Weight (lbs)							
11052	1	0.20	2.35	12	9.40	48	





