

LED Linear Tube

Multi-Function T8 LED U-Bend 2200 Lumen Type A for Electronic Ballast - 5000K



PRODUCT DESCRIPTION

15 watt EarthBulb LED U-Bend tube is available in 5000K with 300 degree beam angle. Great light output and perfect for replacement of T8 u-bend fluorescent tubes. This lamp provides 2200 lumens and has a CRI of 82 and saves over 50% in energy costs. This lamp is engineered for high lumen maintenance over its 50,000 hour rated life. Simply "plug and play" on electronic fluorescent ballasts. For use with instant start, program start, rapid start and emergency back-up ballasts. DLC 4.2 listed. For use on Normal and Low Ballast Factor electronic ballasts only.*

PRODUCT FEATURES

- "Plug and play" on T8 systems utilizing instant start, program start, rapid start and emergency back-up ballasts
- Easily retrofit T8 u-bend, 24 inch tubes with 6 inch leg design
- Provides 2200 lumens
- Chipset provides 5000K daylight with a high color rendering rating of 82
- No Mercury, RoHS Certified
- DLC 4.2 listed

MODEL NUMBER: LT8U15850

ORDERING CODE: 10627

DLC PRODUCT ID: P3FXT5EP

PACK SIZE: 10

DIMENSIONS:

- Diameter: 1 inch
- Nominal Length: 24 inches
- 6 inch "U" design



* Warranty void when lamp is used on high ballast factor electronics fluorescent ballast

Electrical	
Watt	15
Power Factor	> 0.90
Voltage	For use with Instant Start Electronic Ballast
Base Type	G13
Operating Temperature Range	-20°C to 45°C
Light	
Initial Lumens	2200
Lumens per Watt	147
Color Temperature	5000K
Color Rendering (CRI)	82
Beam Angle	300°
Agency Approvals	
UL	Yes
RoHS	Yes
DLC 4.2	Yes
FCC	Yes, FCC 47 Part 18 CLASS A
Product Details	
Warranty *	10 years, 6 hrs/day
Mercury Content	0
Diameter	1"
Nominal Length	24"
Rated Life	50,000 hours