

the ultimate

AIR IMPACT WRENCHES - TITANIUM

• LIGHTWEIGHT • STRENGTH • DURABILITY

2115Ti 3/8"

Light and powerful mini impact wrench



Maximum Torque: 250 ft.-lbs. (280 reverse)

Working Torque: 25 – 230 ft.-lbs.

The lightest, most powerful, 3/8" impact wrench on the market today. At only 142mm long, this tool can be used comfortably in confined spaces. The titanium offers unbeatable strength and durability in the toughest applications and features the proven TwinHammer Plus impact mechanism.



2125QTi 1/2"

Light and powerful mini impact wrenches



Maximum Torque: 250 ft.-lbs. (280 reverse)

Working Torque: 25 – 230 ft.-lbs.

The 1/2" version of the new Model 2115Ti Titanium impact wrench. Superior power in a lightweight package complete with 'Quiet Tool' technology.



2135Ti, 2135Ti-2, 2135QTi & 2135QTi-2 1/2"

A premium technology tool with unbeatable performance



Maximum Torque: 625 ft.-lbs. (700 reverse)

Working Torque: 50 – 600 ft.-lbs.

1000 ft.-lbs of Nut Busting Torque

No other 1/2" impact wrench comes close to the power and performance

of our new TwinHammer 2135 series Titanium impact wrenches. The seven vane motor delivers breakaway torque that will loosen a nut tightened to 1000 ft. lbs.– in mere seconds. Easy to use, one handed forward/reverse push buttons, a professional touch trigger for smooth power delivery and an ergonomically advanced handle for increased comfort and improved grip control. Other features include four position power management control, a through handle exhaust system and 360° swivel inlet.

Available in the following configurations:
Model 2135Ti: with Standard Anvil
Model 2135Ti-2: with 2" Extended Anvil
Model 2135QTi: with 'Quiet Tool' technology
Model 2135QTi-2: with 2" Extended Anvil and 'Quiet Tool' technology



232TGTi 1/2"

The fastest impact wrench



Maximum Torque: 650 ft.-lbs. (625 reverse)

Working Torque: 40 – 400 ft.-lbs.

Legendary ThunderGun performance now available in Titanium for increased durability in a lightweight package. New improved seven vane motor offers increased 10,000 rpm performance to remove the toughest nut. Other features include distinctive racing appearance and adjustable regulator.



2190Ti, 2190Ti-6 & 2190DTi-6 1"

High power and superior ergonomic impact wrenches



Maximum Torque: 1600 ft.-lbs. (1650 reverse)

Working Torque: 150 – 1200 ft.-lbs.

The newest member of the Titanium Team. Designed specifically for tyre changing, the chainsaw handle model provides comfortable control for the operator. The revolutionary handle design allows the operator to grip the tool in a more natural and comfortable position. Minimises bending and squatting with less arm and shoulder back pain. These Titanium models deliver devastating torque in a lightweight package. Weighs 50% less than other 1" impact wrenches. Also available in extended anvil and "D" handle versions. The anvil is made from 25mm high strength steel complete with combination pin hole and "O" ring retention. Other features include TwinHammer mechanism, titanium hammer case, high torque 7 vane motor, convenient 3 position power settings and full power reverse mode, ergonomically advanced handle design and 360° adjustable front handle.



2925Ti Series

Classic IR reliability meets titanium toughness



Ingersoll Rand's line of 2925Ti impacttools have evolved to reflect our new abilities. The new Model 2925 Titanium tools are a blend of our best patented technologies and advanced materials designed to help make your job easier by cutting the toughest bolting jobs down to size. Features include Titanium hammer case, corrosion resistant treatment on internal parts, internal muffler, ergonomic handle, 4 position power regulator, durable textured non-slip grip and solid course thread air inlet.

Pistol Grip

2925P1Ti 3/4"

Maximum Torque: 1450 ft.lbs

Working Torque: 350 – 1100 ft.lbs



2925RBP1Ti 3/4"

Maximum Torque: 1300 ft.lbs (1600 reverse)

Working Torque: 300 – 950 ft.lbs (400 – 1400 reverse)

2925P3Ti 1"

Maximum Torque: 1450 ft.lbs

Working Torque: 350 – 1100 ft.lbs

2925RBP3Ti 1"

Maximum Torque: 1300 ft.lbs (1600 reverse)

Working Torque: 300 – 950 ft.lbs (400 – 1400 reverse)

'D' Handle

2925B2Ti 1"

Maximum Torque: 1600 ft.lbs

Working Torque: 350 – 1400 ft.lbs



2925RB2Ti 1"

Maximum Torque: 1500 ft.lbs (1700 reverse)

Working Torque: 300 – 1300 ft.lbs (400 – 1500 reverse)

3900Ti Series

A new generation of power



Ingersoll Rand's line of 3900Ti impacttools offer the strongest, most durable, longest life mechanism in the world. The new 3900Ti series features include Titanium hammer case, twin hammer mechanism, reverse biased brass end-plates, integrated muffler, integrated reverse lever and high performance 7 vane motor. Each product is laser etched with product information that will last the life of the tool.

3940B2Ti 1"

Maximum Torque: 2500 ft.lbs (2750 reverse)

Working Torque: 500 – 1650 ft.lbs
(500 – 1800 reverse)



3942B2Ti 1"

Maximum Torque: 2750 ft.lbs (3250 reverse)

Working Torque: 1000 – 1800 ft.lbs (1000 – 2100 reverse)

'Q' Models - Quiet Technology

Quiet technology utilises the reflective method of noise reduction. This technology when applied does not clog or degrade the tool performance or restrict air flow or create back pressure. The baffle does not wear out or need to be replaced.

