




Figure similar

Enclosure:

Number of command points	1
Delivery state	
• as a kit	No

Actuator:

Product expansion optional Light source	Yes
Material of the actuating element	plastic
Number of contact modules	1
Type of unlocking device	without
Number of switching positions	2

Front ring:

Product component front ring	Yes
Design of the front ring	standard
Material of the front ring	metal

Contact block/ lampholder:

Number of lampholders	1
-----------------------	---

Display:

Number of LED modules	0
-----------------------	---

General technical data:

Product function	
• positive opening	Yes
Product component	
• lamp transformer	No
• Light source	Yes
Insulation voltage	
• Rated value	600 V
Surge voltage resistance Rated value	4 kV
Thermal current	10 A
Protection class IP	IP66
• of the terminal	IP20

Supply voltage:

Type of voltage of the supply voltage	
• of the light source	AC/DC
Supply voltage 1 of the light source at AC	
• at 60 Hz Rated value	120 V
Supply voltage 1 of the light source at DC	
• Rated value	120 V

Auxiliary circuit:

Number of NC contacts	
• for auxiliary contacts	1
Number of NO contacts	
• for auxiliary contacts	1
Operating current at AC-15	
• at 110 V Rated value	60 A
• at 230 V Rated value	30 A
• at 400 V Rated value	15 A
• at 500 V Rated value	12 A

Connections/ Terminals:

Type of electrical connection	screw-type terminals
Tightening torque [lbf·in]	
• with screw-type terminals	8 ... 8 lbf·in

Lamp:

Color of the light source	clear
----------------------------------	-------

Ambient conditions:

Ambient temperature	
• during operation	-35 ... +70 °C
• during storage	-40 ... +85 °C

Installation/ mounting/ dimensions:

Shape of the installation opening

round

Certificates/ approvals:

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PT6E3A>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52PT6E3A>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52PT6E3A&lang=en

last modified:

17.07.2015