






CADDY® SLICK NUT – SLICK375



- Provides fast universal attachment of threaded rod and hardware to standard strut profiles



Part Number	SLICK375
Material	Spring Steel
Finish	CADDY® ARMOUR
Hole Size (HS)	3/8"
Hole Type	Threaded
Height (H)	11/16"
Torque (TQ)	10 ft lb
Static Load 1 (F1)	600 lb
Static Load 2 (F2)	100 lb
Static Load 3 (F3)	250 lb
Standard Packaging Quantity	100 pc
UPC	78285641672
UNSPSC	31161708
ETIM	EC000096

Indicated loads are independent of the threaded stud or rod.

Indicated loads are applicable on 14 GA and 12 GA (2 mm and 2.5 mm) strut channels only.

WARNING

ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

Copyright © 2013 ERICO International Corporation. All rights reserved.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.

