



1695A Coax - Low Loss Serial Digital Coax



For more information please
call

1-800-Belden1

See Put-ups and Colors

Description:

RG-6/U type, 18 AWG solid .040" bare copper conductor, plenum, foam FEP insulation, Duofoil® + tinned copper braid shield (95% coverage), Flamarrest® jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Coax	1
Total Number of Conductors	1
RG Type	6/U
AWG	18
Stranding	Solid
Conductor Diameter	.040 in.
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material Trade Name	Teflon®
Insulation Material	FFEP - Foam Fluorinated Ethylene Propylene
Insulation Diameter	.170 in.

OUTER SHIELD:

Outer Shield Material Trade Name	Duofoil®
Outer Shield Type	Tape/Braid

Outer Shield Material :

Layer Number	Trade Name	Type	Material	% Coverage (%)
1	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	95

Outer Shield % Coverage	100 %
-------------------------	-------

OUTER JACKET:

Outer Jacket Material Trade Name	Flamarrest®
Outer Jacket Material	LS PVC - Low Smoke Polyvinyl Chloride

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.234 in.
--------------------------	----------



1695A Coax - Low Loss Serial Digital Coax

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +75°C
UL Temperature Rating	75°C
Bulk Cable Weight	33 lbs/1000 ft.
Max. Recommended Pulling Tension	92 lbs.
Min. Bend Radius (Install)	2.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMP
CEC/C(UL) Specification	CMP
EU CE Mark (Y/N)	No
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005

FLAME TEST:

UL Flame Test	NFPA 262
---------------	----------

SWEEP TEST:

Sweep Testing	100% Sweep tested 5 MHz to 3 GHz.
---------------	-----------------------------------

SUITABILITY:

Suitability - Indoor	Yes - All colors
Suitability - Outdoor	Yes - Black only
Suitability - Aerial	Yes - Black only, when supported by messenger wire
Suggested Connectors	Amphenol 31-70000; Kings 2065-9-9; ADC BNC-1695D; Amp 1-221185-6

PLENUM/NON-PLENUM:

Plenum (Y/N)	Y
Non-Plenum Number	1694A

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	75 Ohms
Nom. Inductance	0.103 µH/ft
Nom. Capacitance Conductor to Shield	16.1 pF/ft
Nominal Velocity of Propagation	82 %
Nominal Delay	1.24 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	6.4 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20°C	2.8 Ohms/1000 ft
Minimum Structural Return Loss :	

1695A Coax - Low Loss Serial Digital Coax

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Minimum Structural Return Loss (dB)
		5	850	23
		851	3000	21

Nom. Attenuation :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	1			0.24
	3.58			0.45
	5			0.55
	7			0.65
	10			0.75
	67.5			1.74
	71.5			1.78
	88.5			1.94
	100			2.1
	135			2.4
	143			2.5
	180			2.8
	270			3.4
	360			4.0
	540			5.2
	720			6.1
	750			6.2
	1000			7.3
	1500			9.2
	2000			10.9
	2250			11.6
	3000			13.7

Max. Operating Voltage - UL

300 V RMS

Other Electrical Characteristic 1

Impedance tested in accordance with ASTM D-4566 paragraph 43.2, option 2 using a 75 Ohm fixed bridge and termination.

Other Electrical Characteristic 2

Return Loss tested in accordance with ASTM D-4566 paragraph 45.3, using a 75 Ohm fixed bridge and termination.

NOTES:

Notes

Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
1695A 0011000	#18 FFEP SH FLRST	1000	45	BROWN	C
1695A 0021000	#18 FFEP SH FLRST	1000	45	RED	C

1695A Coax - Low Loss Serial Digital Coax

1695A 0031000	#18 FFEP SH FLRST	1000	45	ORANGE	C
1695A 0041000	#18 FFEP SH FLRST	1000	45	YELLOW	C
1695A 0061000	#18 FFEP SH FLRST	1000	45	BLUE, LIGHT	C
1695A 0071000	#18 FFEP SH FLRST	1000	45	VIOLET	C
1695A 0081000	#18 FFEP SH FLRST	1000	45	GRAY	C
1695A 0101000	#18 FFEP SH FLRST	1000	45	BLACK	C
1695A 010500	#18 FFEP SH FLRST	500	22	BLACK	C
1695A 8771000	#18 FFEP SH FLRST	1000	45	NATURAL	C
1695A 877500	#18 FFEP SH FLRST	500	20.5	NATURAL	Z
1695A N3U1000	#18 FFEP SH FLRST	1000	45	GREEN, MIL	C

C = CRATE REEL PUT-UP.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 4 Revision Date: 08-24-2005

© 2005 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden CDT Electronics Division believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.