Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



8668 Hook-up/Lead - Shielding and Bonding Cable

For more Information please call

1-800-Belden1



Description:

Shielding and Bonding Cable.

Physical Characteristics (Overall)

Conductor

AWG:

AWG	Stranding	Conductor Material
13.3	120x34	Braided TC - Braided Tinned Copper

Braided Tubular I.D.: 0.170 in.

Circular Mil Area (CMA): 4800

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

	EU Directive 2000/53/EC (ELV):	Yes		
	EU Directive 2002/95/EC (RoHS):	Yes		
	EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004		
	EU Directive 2002/96/EC (WEEE):	Yes		
	EU Directive 2003/11/EC (BFR):	Yes		
	CA Prop 65 (CJ for Wire & Cable):	Yes		
	MII Order #39 (China RoHS):	Yes		
Plenum/Non-Plenum				
	Plenum (Y/N):	No		

Electrical Characteristics (Overall)

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft) 2.17

Max. Recommended Current:

Current 36.0

Notes (Overall)

Notes: AWG size is approximated.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8668 000250	250 FT	5.000 LB	NONE		11/64" ID TUBULAR BRD TC
8668 00050	50 FT	1.050 LB	NONE		11/64" ID TUBULAR BRD TC

Page 1 of 2 06-16-2010

Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



8668 Hook-up/Lead - Shielding and Bonding Cable

Revision Number: 1 Revision Date: 05-14-2007

© 2010 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.