

General Purpose Multi-Conductor Non-Shielded Plenum



SPECIFICATIONS



APPLICATIONS

- Audio
- Control
- Instrumentation

CONSTRUCTION

Conductor: Stranded tinned copper
 Insulation: Smokeguard or PVC
 Outer Jacket: PVC Jacket, grey
 Temperature: -20°C to 80°C
 Options: Stranded bare copper conductors
 Other coloured outer jacket and constructions available upon request

Part Number	Conductor			Approx. Diameter (in.)	Volt	Approx Weight (LB/MFT)	Colour Code Chart
	No.	AWG Size	Stranding				
52-226-2202	2	22	7/30	0.123	300	9	Black/Red
52-226-2203	3	22	7/30	0.131	300	12	Black/Red/Green
52-226-2204	4	22	7/30	0.140	300	15	1
52-226-2206	6	22	7/30	0.162	300	22	1
52-226-2209	9	22	7/30	0.184	300	32	1
52-226-1802	2	18	7/26	0.161	300	18	Black/Red
52-226-1803	3	18	7/26	0.172	300	25	1
52-226-1804	4	18	7/26	0.189	300	32	1
52-226-1805	5	18	7/26	0.209	300	39	1
52-226-1806	6	18	7/26	0.230	300	46	1
52-226-1808	8	18	7/26	0.239	300	61	1
52-226-1810	10	18	7/26	0.266	300	75	1
52-226-1602	2	16	19/29	0.191	300	24	2
52-226-1603	3	16	19/29	0.203	300	33	2
52-226-1604	4	16	19/29	0.216	300	43	2
52-226-1402	2	14	19/26	0.227	300	38	Black/Red
52-226-1403	3	14	19/26	0.232	300	49	2
52-226-1404	4	14	19/26	0.291	300	70	2

Note: All dimensions are nominal and are subject to normal manufacturing tolerance. Specifications are subject to change without prior notice

*See page 32 for corresponding Colour Code Chart