

General Purpose Multi-Conductor Cont'd

Stranded Conductor

Part Number	Conductor			Approx. Diameter (in.)	Volt	Approx Weight (LB/KM)	Colour Code Chart
	No.	AWG Size	Stranding				
52-224-1806	6	18	16/30	0.255	600	59	1
52-224-1807	7	18	16/30	0.265	600	67	1
	8	18	16/30	0.286	600	77	1
52-224-1809	9	18	16/30	0.300	600	83	1
52-224-1812	12	18	16/30	0.353	600	110	2
52-224-1815	15	18	16/30	0.386	600	134	2
52-224-1819	19	18	16/30	0.429	600	167	2
52-224-1825	25	18	16/30	0.485	600	209	2
52-224-1830	30	18	16/30	0.524	600	247	2
52-224-1840	40	18	16/30	0.633	600	350	2
52-224-1602	2	16	26/30	0.226	600	36	2
52-224-1603	3	16	26/30	0.240	600	48	2
52-224-1604	4	16	26/30	0.263	600	61	2
52-224-1605	5	16	26/30	0.277	600	77	2
52-224-1607	7	16	26/30	0.343	600	104	2
52-224-1609	9	16	26/30	0.380	600	130	2
52-224-1612	12	16	26/30	0.430	600	168	2
52-224-1615	15	16	26/30	0.473	600	202	2
52-224-1619	19	16	26/30	0.524	600	251	2
52-224-1625	25	16	26/30	0.633	600	352	2
52-224-1402	2	14	41/30	0.320	600	65	2
52-224-1403	3	14	41/30	0.338	600	85	2
52-224-1404	4	14	41/30	0.369	600	107	2
52-224-1405	5	14	41/30	0.402	600	134	2
52-224-1407	7	14	41/30	0.438	600	167	2
52-224-1408	8	14	41/30	0.475	600	210	2
52-224-1409	9	14	41/30	0.438	600		2
52-224-1412	12	14	41/30	0.620	600	299	2
52-224-1415	15	14	41/30	0.666	600	368	2
52-224-1202	2	12	65/30	0.386	600	95	2
52-224-1203	3	12	65/30	0.411	600	130	2
52-224-1204	4	12	65/30	0.454	600	164	2
52-224-1205	5	12	65/30	0.463	600	177	2
52-224-1207	7	12	65/30	0.526	600	261	2
52-224-1002	2	10	105/30	0.464	600	134	Black/Red

Note: All dimensions are nominal and are subject to normal manufacturing tolerance.
 Specifications are subject to change without prior notice

*See page 32 for corresponding Colour Code Chart