

Welding Cable



APPLICATION

Welding

CONSTRUCTION

Conductor: Extra flexible stranded bare copper conductors

Jacket: EPDM (Ethylene Propylene Diene Monomer), black or red

Temperature: -50°C to 105°C

Package Qty: 152m (500ft.) or 76m (250ft.) reels

Voltage: 600V

Feature: Resistant to chemicals, oil, acid, water, ozone, sunlight and abrasion

Option: Other coloured outer jacket and constructions available upon request

Basic Part Number	Conductor		Approx. Wall Thickness	Approx. Diameter (in.)	Approx Weight (LB/MFT)	Part # Colour Code			
	AWG Size	Stranding				Black	010	Red	030
08011-02	6	266/30	0.060	0.320	116				
08011-03	4	392/30	0.060	0.375	163	Add colour code to the basic part number e.g. 08011-08-010 is a 2/0 black Welding Cable			
08011-05	2	644/30	0.060	0.440	251				
08011-06	1	784/30	0.080	0.515	321				
08011-07	1/0	1026/30	0.080	0.550	388				
08011-08	2/0	1254/30	0.080	0.590	474				
08011-09	3/0	1615/30	0.080	0.660	601				
08011-10	4/0	2052/30	0.080	0.725	762				

See page 27 for the Suggested Minimum Copper Welding Cable Size

Note: All dimensions are nominal and are subject to normal manufacturing tolerance.
Specifications are subject to change without prior notice