


Ultraflex Split Loom Polyethylene



APPLICATION

- Mechanical, chemical and electrical protection

CONSTRUCTION

- Material:** Durable Polyethylene, black
- Construction:** Slit allows quick installation without the need of fishing wires
- Variation:** Non-slit also available to give a better protection from environmental elements
- Temperature:** -40°C to 93°C
- Feature:** Resistant to oil and gas, moisture, UV light, salt and abrasion
- Option:** Packaged in 2'sq boxes or 4'sq gaylords. Cut to length packaging also available
Other colours available upon request

Box Part Number Approx. 30 lbs	Gaylord Part Number Approx. 200 lbs	Size (in.)	Inside Diameter (in.)		Outside Diameter (in.)	
			Min	Max	Min	Max
06-804S-A	06-LCP-250	1/4	.237	.266	.375	.400
06-806S-A	06-LCP-350	3/8	.341	.380	.497	.526
06-808S-A	06-LCP-500	1/2	.473	.516	.664	.700
06-810S-A	06-LCP-625	5/8	.603	.639	.805	.837
06-812S-A	06-LCP-750	3/4	.707	.759	.950	.989
06-814S-A	06-LCP-875	7/8	.848	.898	1.107	1.151
06-816S-A	06-LCP-1000	1	1.006	1.055	1.267	1.320
06-820S-A	06-LCP-1250	1-1/4	1.199	1.257	1.446	1.500
06-824S-1	06-LCP-1500	1-1/2	1.566	1.647	1.867	1.947

Ultraflex Split Loom Nylon



APPLICATION

- Mechanical, chemical and electrical protection where high temperature is required

CONSTRUCTION

- Material:** Durable Nylon, black with grey stripe
- Temperature:** -40°C to 149°C
- Construction:** Slit allows quick installation without the need of fishing wires
- Feature:** Resistant to oil and gas, moisture, UV light, salt and excellent high temperature and abrasion protection
- Option:** Packaged in 2'sq boxes or 4'sq gaylords. Cut to length packaging also available
Other colours available upon request
Non-slit also available (allows for better protection from environmental elements)

Box Part Number Approx. 30 lbs	Gaylord Part Number Approx. 200 lbs	Size (in.)	Inside Diameter (in.)		Outside Diameter (in.)	
			Min	Max	Min	Max
06-LCN-250-BOX	06-LCN-250	1/4	.237	.266	.375	.400
06-LCN-350-BOX	06-LCN-350	3/8	.341	.380	.497	.526
06-LCN-500-BOX	06-LCN-500	1/2	.473	.516	.664	.700
06-LCN-625-BOX	06-LCN-625	5/8	.603	.639	.805	.837
06-LCN-750-BOX	06-LCN-750	3/4	.707	.759	.950	.989
06-LCN-875-BOX	06-LCN-875	7/8	.848	.898	1.107	1.151
06-LCN-1000-BOX	06-LCN-1000	1	1.006	1.055	1.267	1.320
06-LCN-1250-BOX	06-LCN-1250	1-1/4	1.199	1.257	1.446	1.500
06-LCN-1500-BOX	06-LCN-1500	1-1/2	1.566	1.647	1.867	1.947

Note: All dimensions are nominal and are subject to normal manufacturing tolerance – Specifications are subject to change without prior notice