

## Ultraflex Brake Light Cable



### APPLICATION

Brake Light

### CONSTRUCTION

**Conductor:** Solid bare copper conductors, flat, black & white

**Insulation:** Polyvinyl Chloride (PVC)

**Outer Jacket:** Flame-retardant, moisture and sunlight resistant PVC, black

**Temperature:** -40°C to 80°C

**Voltage:** 50V

**Options:** Other coloured outer jacket and inner conductors available upon request  
Other constructions available

Part Number	Conductor			Approx. Insulation Thickness (in.)	Approx. Jacket Thickness (in.)	Approx. Diameter (in.)	Approx Weight (LB/MFT)	Package Qty			Colour Code
	No.	AWG Size	Stranding					76m (250ft.)	152m (500ft.)	305m (1,000ft.)	
26400-01-000	2	18	16	0.023	0.030	0.153x0.240	29	◆	◆	◆	Black & White
26400-02-000	2	16	24	0.023	0.030	0.154x0.260	38	◆	◆	◆	Black & White
26400-02-053	2	16	24	0.023	0.030	0.154x0.260	38	◆	◆	◆	Green & Red
26400-02-090*	2	16	24	0.023	0.030	0.170x0.276	38	◆	◆	◆	Black & White
26400-03-000	2	14	41	0.023	0.030	0.198x0.322	51	◆	◆	◆	Black & White
26400-03-090*	2	14	41	0.023	0.030	0.198x0.322	51	◆	◆	◆	Black & White
26400-04-041	2	12	65	0.023	0.030	0.219x0.362	72	◆	◆	◆	Black & Blue
26400-04-042	2	12	65	0.023	0.030	0.219x0.362	72	◆	◆	◆	Black & White
26400-05-000	2	10	105	0.023	0.030	0.227x0.388	104	◆	◆	◆	Blue & Black

\*Gray Jacket

Note: All dimensions are nominal and are subject to normal manufacturing tolerance.  
Specifications are subject to change without prior notice