

# Foot Switches

Linemaster

## Clipper



Single



TWIN

Catalog Number	Description	Circuit	Electrical Rating
<b>632-S</b>	Momentary	SPDT	20A @ 125-250VAC
<b>642-S</b> (wide treadle)			1 H.P. @ 125-250VAC
<b>635-S**</b>	Momentary	DPDT	15A @ 125VAC / 10A @ 250VAC
<b>645-S**</b> (wide treadle)			1/2 H.P. @ 125-250VAC
<b>636-S**</b>	Two Stage	Each Stage	15A @ 125VAC / 10A @ 250VAC
<b>646-S**</b> (wide treadle)	Momentary	SPDT	1/2 H.P. @ 125-250VAC
<b>632-DA</b>	Maintained	SPDT	20A @ 125-250VAC
<b>642-D</b> (wide treadle)			1 H.P. @ 125-250VAC
<b>632-SC3*</b>	Momentary	SPST Wired N.O.	15A @ 125VAC 1/2 H.P. @ 125VAC
<b>634-DA**</b>	Maintained	DPDT	10A @ 125VAC / 5A @ 250VAC
<b>TWIN-632-S</b>	Momentary	Each Side SPDT	20A @ 125-250VAC 1 H.P. @ 125-250VAC
<b>TWIN-635-S**</b>		Each Side DPDT	15A @ 125VAC / 10A @ 250VAC 1/2 H.P. @ 125-250VAC

- Cast Iron Housing with Nonskid Base Pad
- Painted Black
- 4-1/2" x 3-1/2" x 1-1/2" • 2-1/4 Lbs
- Wide Treadle 7" • 3-1/2 Lbs.
- Momentary Models - Press to Start - Release to Stop
- Maintained Models - Press to Start - Press to Stop
- \* Supplied with 8 ft. 14/3 Cord and 3 Prong Series Plug
- Green Lead Grounded

- TWIN Models consist of two SPDT or two DPDT switches mounted on a heavy steel base plate with nonskid pad. Divider bar between pedals helps prevent accidental operation of both pedals at one time. A tube between the two switches conceals all internal wiring between them. A conduit opening with strain relief connector is provided on the right switch.
- TWIN Models 8-3/4" x 4-1/2" x 1-1/2" • 5 Lbs

Optional Guards Available - See page 17



## Aqualine



Catalog Number	Colour	Description	Circuit	Electrical Rating
<b>971S</b>	Dark Gray	Momentary	SPDT	15A 125-250VAC 1/2 H.P. @ 125-250VAC
<b>971SA</b>	Light Gray			
<b>971SB</b>	Blue			
<b>971SO</b>	Orange			
<b>971SY</b>	Yellow	Momentary	DPDT	15A 125-250VAC 1/2 H.P. @ 125-250VAC
<b>974S</b>	Dark Gray			
<b>974SA</b>	Light Gray			

- Rustproof and corrosion proof polymeric material and formed steel base
- Non skid base pad
- Raised ribs on treadle for positive traction during operation
- 2 holes provided for rigid mounting to floor or equipment

- Integrated adjustable strain relief clamp accommodates cord sizes from .250 Dia. To .400 Dia.
- 3.44" x 4" x 1.16" • 3.6 oz.
- Momentary - Press to Start - Release to Stop
- IP20

Optional Guards Available - See page 17

