



Clamps

Type JAB — Ground Rod Clamps

- Cast of high-strength corrosion resistant copper alloy
- Both hex head and socket set screws available
- Long bearing surface of clamp on ground wire secures ground connection
- Listed for direct burial



Cat. No.		Nominal Rod Dia.		Wire Range				Dimensions (in.)							
Socket Set Screw	Hex Head Bolt	(in.)	(mm)	Max.	Min.	Max. (mm²)	Min. (mm²)	A (Max.) Socket Screw	A (Max.) Hex Bolt	Screw Thread Size UNC-2A	B	C	D		
JAB12*	JAB12H	1/2	12.7	2 str.	10 sol.	33.6	5.2	1-19/32	2-3/32	7/16-14	27/32	7/8	19/32		
JAB58	JAB58H	5/8	15.8	1/0 str.	8 sol.	53.4	8.3	1-27/32	2-13/64		29/32	1	11/16		
JAB34	JAB34H	3/4	19.0					2	2-11/32		11/16		51/64		
—	JAB34C	3/4 + 5/8	15.8 to 19.0	3/0 str.				—	—		1-1/8	1-1/32	13/16		
JAB1	JAB1H	1	25.0					2-1/4	3		1-11/32	1-1/16	1		

* CSA not applicable.
Add suffix P to Cat. No. for tin-plated clamp.

Type G — Budget Line Ground Clamps

- A dependable ground connection offered at a substantial saving
- Cast of high-strength corrosion-resistant copper alloy
- Hex head bolts
- Simplified compact design will make a lasting, trouble-free connection
- Listed for direct burial



Cat. No.	Nominal Rod Dia.		Wire Range				Dimensions (in.)					
	(in.)	(mm)	Max.	Min.	Max. (mm²)	Min. (mm²)	A (Max.) Bolt	Screw Thread Size UNC-2A	B	C	D	E
G3*	3/8	9.5	4 str.	10 sol.	21.1	5.2	1-3/8	5/16-18	11/16	1/2	27/64	3/8
G4	1/2	12.7	2 str.		33.6		—	3/8-16	27/32	3/8	43/64	13/16
G5	5/8	15.8							29/32			
G6	3/4	19.0							1-1/16			

* Not U.L. Listed and CSA not applicable.
Add suffix P to Cat. No. for tin-plated clamp.

