

Nonmetallic Sheathed Cable

Fittings



Cat. No.	Trade Size (in.)	Clamping Range (in.)		Suggested Application
		Min.	Max.	
One Screw Fittings (Zinc Alloy)				
				NMD90 (loomex)
L-16	3/8	0.12	0.63	14/2, 14/3, 12/2, 12/3, 10/2
CI70	3/8	0.13	0.70	14/2-10/2; 14/3-10/3
CI71	1/2	0.33	0.95	8/2-4/2; 12/3-4/3
CI72	3/4	0.60	1.15	4/2-3/2; 4/3-3/3
CI73	1	0.93	1.47	2/2; 2/3
Two Screw Fittings (Zinc Alloy)				
CI804	3/8	0.18	0.64	14/2-10/2; 2# 14/2 and 2# 12/2
CI806	3/4	0.41	0.82	8/2-6/3
CI808	1	0.50	1.04	4/2-2/2; 8/3-4/3
CI810	1-1/4	0.56	1.06	4/2-2/2; 8/3-4/3
CI812	1-1/2	0.63	1.60	4/2-2/2; 8/3-2/3
CI816	2	0.86	2.06	3/2-2/2; 6/3-2/3
Two Screw Fittings (Steel)				
CI2060	3/8	0.11	0.60	14/2-10/2; 14/3-10/3
CI2061	3/4	0.15	0.90	10/2-6/2; 10/3-6/3
One Screw Fittings (Zinc Alloy)				
CI2163	3/8	0.35	0.61	10/3

CI70



Zinc Die Cast Locknut

L-16



Zinc Die Cast Locknut

CI71 / CI73



Zinc Die Cast Locknut

CI804



Die Cast Locknut

CI806



Zinc Die Cast Locknut

CI808 / CI816



Zinc Die Cast Locknut

CI2060 / CI2061



Zinc Die Cast Locknut

CI2163



Zinc Die Cast Locknut

All NMD90 fittings are also suitable for NMWU90 of equivalent diameters, in dry locations. **NOTE:** 3/8 in. trade size connectors require a 1/2 in. knockout

Technical improvements are constantly taking place in the electrical industry. Cable manufacturers are changing their products from time to time. Accordingly, it is strongly suggested that you verify the cable size with the cable manufacturer prior to selecting a fitting.

Nonmetallic Sheathed Cable

Connectors



Cat. No.	Trade Size (in.)	Clamping Range (in.)		Suggested Application
		Min.	Max.	
One Screw Fittings (Aluminum)				
CI2166	1/2	0.50	0.90	8/3-6/3
CI2167	3/4	0.71	1.10	6/3-4/3
Duplex Fittings (Zinc Alloy)				
One Screw CI2175	3/8	0.15	0.65	14/2-10/2; 14/3-10/3
Nonmetallic Fittings				
CI3360	1/2	0.30	0.60	14/2-10/2; 14/3-10/3 2 cables: 14/2-12/2
CI4004		0.21	0.42	14/2-10/2; 14/3-10/3 2 cables: 14/2-12/2
W100LX-D		0.21	0.42	14/2-10/2; 14/3-10/3 2 cables: 14/2-12/2
One Screw Fittings (Steel)				
CI4040	3/8	0.19	0.57	14/2-10/2; 14/3-10/3 2 cables: 14/2
CI9049		0.13	0.37	14/2-10/2; 14/3-12/3

CI2166 / CI2167



Zinc Die Cast Locknut

CI2175



Zinc Die Cast Locknut

CI3360



CI4004 / W100LX-D



CI4040



CI9049



All NMD90 fittings are also suitable for NMWU90 of equivalent diameters, in dry locations. **NOTE:** 3/8 in. trade size connectors require a 1/2 in. knockout

Technical improvements are constantly taking place in the electrical industry. Cable manufacturers are changing their products from time to time. Accordingly, it is strongly suggested that you verify the cable size with the cable manufacturer prior to selecting a fitting.

Nonmetallic Sheathed Cable

Accessories



CI10 / CI11



CI1-C



CI0 / CI5



CI1544



CI1544P



CIS-1X2



CIS-1 / CIS-4



CI66-T



CI66



CI66-PPH



CI66-SS



CI66-FPP



CI66-XL-2



CI66-XL



Cat. No.	Dimensions (in.)		Hole Size (in.)	Suggested Application
	H	W		
Cable Straps (Aluminum)				
CI0	0.44	0.63	3/16	14/3-12/3
CI1	0.50	0.56	3/16	10/3
CI1-C	0.50	0.50	3/16	14/2-12/2; 14/3-12/3
CI2	0.50	0.63	3/16	14/3-10/3
CI3	0.57	0.68	3/16	14/3-10/3
CI4	0.81	1.06	3/16	4/3
CI5	1.06	1.25	7/32	3/3-2/3
CI10	0.19	0.44	3/16	14/2
CI11	0.31	0.56	3/16	12/2-10/2
Nailing Straps (Zinc Plated Steel)				
CI1544	0.25	0.51	-	14/2-12/2
Nailing Straps (Polyethylene)				
CI1544-P	0.25	0.49	-	14/2-12/2
CI1546-P	0.25	0.75	-	14/2-8/2
Cable Staples (Galvanized Steel)				
CIS-1	0.25	0.48	-	14/2-12/2
CIS-2	0.44	0.54	-	2 cables 14/2; 2 cables 12/2; 14/2-14/3-12/2-12/3-10/2-10/3
CIS-3	0.49	0.70	-	10/2-8/2; 14/3-10/3
CIS-4	0.76	0.86	-	14/2 - 8/2, 14/3 - 8/3, 14/4 - 10/4
Double Cable Staples (Galvanized Steel)				
CIS-1X2	0.25	0.48 x 2	-	14/2-12/2
CIS-1X2-FP3				
CIS-1X2-FP5				

Also suitable for NMWU90 of equivalent diameters.



Cat. No.	Suggested Application
Protector Plates (Galvanized Steel)	
CI66	For wood stud
CI66-FPP	For forenze
CI66-PPH	For exterior wall, in front of wood stud
CI66-SS	For metal stud
CI66-T	For wood stud
CI66-XL	
CI66-XL-2	

As required by CEC rules 12-516 and 12-616