

ELECTRONIC THERMOSTAT

STE302NP SERIES

1

SINGLE PROGRAMMING

3000 W

INSTALLATION AT YOUR FINGERTIPS!

Thanks to its innovative wall support, the °STELPRO STE302NP thermostat is quick and easy to install. It can be used to control electric heating units with or without fans. It also allows you to lower the temperature at a specified time of the day to ensure absolute comfort, either during nighttime or business hours.



SIMPLE 4-STEP PROGRAMMING

LOWER THE TEMPERATURE AT NIGHT AND AUTOMATICALLY RETURN TO THE SELECTED TEMPERATURE DURING THE DAY



INCREASED SAVINGS AND COMFORT

INCOMPARABLE ACCURACY



BACKLIT SCREEN

MAY BE USED AS A NIGHTLIGHT



CONSUMPTION SAVINGS

ENERGY SAVINGS OF MORE THAN 30% WITH DAY/NIGHT TEMPERATURE REDUCTION OF 4.5 °C (8 °F)

COLOUR

white

FINISH

molded plastic

WATTAGE & VOLTAGE

150 W to 1500 W @ 120 V / 260 W to 2600 W @ 208 V / 300 W to 3000 W @ 240 V

CONTROL

- 2-wire connection
- acts like a programmable thermostat by automatically lowering the temperature once per 24-hour period (Single programming mode)
- compatible with forced-air units (Fan mode)
- frost-free warning
- lock option at a maximum temperature set point (Security mode)
- display in either Celsius or Fahrenheit


ACCURACY

accurate ambient temperature control of ± 0.1 °C (0.18 °F)

TEMPERATURE RANGE

between 3 and 30 °C (37 to 86 °F)

DESIGNED FOR



AND MORE...

TECHNICAL SPECIFICATIONS

PRODUCT	WATTS		VOLTAGE	AMPERAGE	FREQUENCY	PACKAGING	UNIT PRICE
CODE	MINIMUM	MAXIMUM	VOLTS	AMPERES	HZ		
STE302NPWB+	150/260/300	1500/2600/3000	120/208/240	12.5	50/60	BOX	29.50

DIMENSIONS: width of 4 7/8 in. (124 mm), height of 4 7/8 in. (124 mm) and depth of 1 1/8 in. (29 mm)

ELECTRONIC THERMOSTAT

STE302P SERIES

M

MULTIPLE PROGRAMMING

3000 W

THE SMART, EFFICIENT AND ECOLOGICAL CHOICE

Cost-saving programming, that's what the STE302P thermostat has to offer. Life just got both simpler and more comfortable thanks to its Preprogrammed mode that allows you to easily and quickly program the desired temperature. Offering 18 predefined programs, the user can easily select among the most commonly used settings or program their own custom settings.



18

EASY PROGRAMMING

INCLUDES 18 PREPROGRAMMED PRESETS
IN "PRE-PROG" MODE

±
0.1°C

INCREASED SAVINGS AND COMFORT

INCOMPARABLE ACCURACY



ANTICIPATED START

REACH THE SELECTED TEMPERATURE
AT PRECISELY THE PROGRAMMED TIME

5-2

5-2 DAY PROGRAMMING



BACKLIT SCREEN

MAY BE USED AS A NIGHTLIGHT

MORE THAN
30%

CONSUMPTION SAVINGS

ENERGY SAVINGS OF MORE THAN
30% WITH DAY/NIGHT TEMPERATURE
REDUCTION OF 4.5 °C (8 °F)

COLOUR

white

FINISH

molded plastic

WATTAGE & VOLTAGE

150 W to 1500 W @ 120 V / 260 W to 2600 W @ 208 V / 300 W to 3000 W @ 240 V

CONTROL

- 2-wire connection
- compatible with forced-air units (Fan mode)
- easily choose the desired preprogramming with one button
- able to program 4 periods a day during the week and 4 others per day during the weekend, for a maximum of 8/week
- anticipated start (the thermostat reaches the desired temperature at the requested hour)
- frost-free warning
- lock option at a minimum and maximum temperature set point (Security mode)
- protection against power failure (2 hours)
- the hour can be displayed in 12 or 24-hour mode
- display in either Celsius or Fahrenheit

ACCURACY

accurate ambient temperature control of ± 0.1 °C (0.18 °F)

TEMPERATURE RANGE

between 3 and 30 °C (37 to 86 °F)

DESIGNED FOR



AND MORE...

TECHNICAL SPECIFICATIONS

PRODUCT		WATTS		VOLTAGE	AMPERAGE	FREQUENCY	PACKAGING	UNIT PRICE
CODE	MINIMUM	MAXIMUM	VOLTS	AMPERES	HZ			
STE302PWB+	150/260/300	1500/2600/3000	120/208/240	12.5	50/60		BOX	40.00

DIMENSIONS: width of 4 7/8 in. (124 mm), height of 4 7/8 in. (124 mm) and depth of 1 1/8 in. (29 mm)



*STELPRO reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. Returns are not accepted for orders of products with optional colours. For all the latest models and updated prices, please refer to our web site at www.stelpro.com.