

# iGen1200

## 1200 Watt Digital Inverter Gasoline Portable Generator

1000 Running Watts | 1200 Peak Watts



50 State and  
Canada Model



Built-in carry handle  
for easy transportation

Fuel efficient, .8 gallon fuel tank  
that runs 9 hrs at 25% load

Simple access panel for  
easy maintenance

Two 5V USB ports for charging  
sensitive electronics such as  
phones or tablets


Rubber outlet dust covers



Dependable 1.8 HP 54cc OHV  
4-Stroke Westinghouse engine



Double-insulated acoustic  
enclosure and low tone mufflers  
to reduce operating noise



Parallel capable with another  
iGen using WHPC (additional  
generator and WHPC cord  
sold separately)

<3% THD  
SINE WAVE OUTPUT

120V AC 20A  
5-20R OUTLETS  
WITH COVER

LOW OIL,  
OVERLOAD &  
OUTPUT READY  
LIGHTS

20A CIRCUIT  
BREAKER

5V DC USB  
PORTS WITH  
COVER

EFFICIENCY  
MODE

OVERLOAD  
RESET

GROUND  
RESET



### What Comes in the Box



# iGen1200

## Inverter Generator Specifications



Gasoline Peak Watts	1200
Gasoline Running Watts	1000
Peak Amps at 120V	10A
Running Amps at 120V	8.3A
AC Voltage	120 Volts
DC Voltage	5 Volts
AC Frequency	60 Hz
Parallel Capable with WHPC cord (sold separate)	Yes
Engine Horse Power (HP)	1.8 HP
Total Harmonic Distortion (THD)	<3%
Automatic Voltage Regulator (AVR)	Yes
Starting System	Recoil
Battery	No
Engine Displacement	54cc
Engine Brand	Westinghouse
Engine Type	OHV 4 Stroke
Engine Speed	Variable
Engine RPM	Max 5000
Available in True Timber Camo	No
Operational Volume	as low as 52 dBA
Spark Plug (included)	Torch A5RTC
Carburetor Kit Required to Operate at Altitude	Yes
Altitude Carburetor Kit Number (sold separate)	140499
Economy Mode Switch	Yes
Built-in Inverter	Yes
Engine Lubrication	Splash
Recommended Oil	SAE 10W30
Oil Bottle Size (included)	.25 qt. (11.8 oz.)
Oil Capacity (Quarts/Ounces)	.25 qt. (11.8 oz.)
Low Oil Shutdown	Automatic
Fuel Type	Unleaded Gasoline, 10% Ethanol or less
Fuel Shut Off	Manual
Fuel Tank Material	Plastic
Fuel Tank Capacity (Gallons/Liters)	.8 gal. (3 L)

Run Time at %25 Load (hrs.)	9 hrs.
Run Time at %50 Load (hrs.)	7 hrs.
Gasoline Fuel Gauge	No
Choke type	Manual
Choke Location	Side Panel
AC Outlets	(1) Duplex 120V 20A (5-20R)
DC Outlets	(2) 5V USB ports
Ground	Floating Neutral
Covered Outlets	Yes
Transfer Switch Ready	No
Westinghouse Portable Transfer Switch Ready (ST Switch)	No
Voltmeter	No
GFCI Outlets	No
LED Data Center	No
RV Ready Outlet	No
Overload Protection (circuit breaker)	Yes
Handle Style	Single, molded in case
Wheel Kit	No
Emissions	EPA, CARB
Canada CSA Compliant	Yes
Muffler	Pulse-Flo™
Spark Arrestor	Yes
Residential Warranty	3 Years
Commercial Warranty	1 Year
Assembled Length in. (mm)	18 in. (457mm)
Assembled Width in. (mm)	10 in. (254mm)
Assembled Height in. (mm)	15.5 in. (394 mm)
Carton Length in. (mm)	20 in. (508 mm)
Carton Width in. (mm)	12 in. (305 mm)
Carton Height in. (mm)	16.5 in. (419 mm)
Dry Unit Weight lb. (kg)	33 lb. (15 kg)
Shipping Weight lb. (kg)	36.3 lb. (16.5 kg)
UPC	855464003872
GTIN	00855464003872

09102018KD  
 ©2018 Westinghouse Portable Power  
 Specifications are subject to change without notice  
 Westinghouse Portable Power  
 777 Manor Park Dr., Columbus, OH 43228

**Have questions? Contact our team  
 at [service@wpowereq.com](mailto:service@wpowereq.com) or call  
 855.944.3571**

