

RTD and Thermocouple Modules



Specialty modules are available for RTD and Thermocouple inputs. Modules require a carrier base (IC200CHSxxx).

	IC200ALG620	IC200ALG630
Product Name	VersaMax Analog Input Module, 16 Bit RTD, 4 Channel	VersaMax Analog Input Module, 16 Bit Thermocouple, 7 Channel
Lifecycle Status	Active	Active
Input Range	RTD types: 25, 100, and 1000 ohm platinum 10, 50, and 100 ohm copper 100 and 120 ohm nickel 604 ohms nickel/iron	Thermocouple types: J, K, T, S, R, none (used for mV inputs)
Number of Channels	4	7
Resolution	15 bits plus sign	15 bits plus sign
Update Rate	60 Hz: approximately 210 milliseconds per channel 50 Hz: approximately 230 milliseconds per channel	60 Hz: approximately 60 milliseconds per channel 50 Hz: approximately 70 milliseconds per channel
Accuracy at 25°C	on voltage measurement: $\pm 0.15\%$ on resistance measurement on temperature measurement: $\pm 0.15\%$ on RTD (temperature) measurement	on voltage measurement: $\pm 0.2\%$ on temperature measurement: $\pm 0.15\%$
5 V Backplane Current Consumption (mA)	125 maximum	125 maximum
3.3 V Backplane Current Consumption (mA)	125 maximum	125 maximum
LED Indicators	OK LED: green indicates backplane power is present. Amber indicates module fault.	OK LED: green indicates backplane power is present. Amber indicates module fault.
Dimensions (W x H x D)	110 mm (4.3 in) x 66.8 mm (2.63 in) x 50 mm (1.956 in), not including the height of the carrier or the mating connectors	110 mm (4.3 in) x 66.8 mm (2.63 in) x 50 mm (1.956 in), not including the height of the carrier or the mating connectors