



## Carriers

VersaMax provides several types of snap-together I/O carriers and interposing terminals to provide maximum wiring flexibility, as well as module hot insertion and removal. VersaMax carriers support IEC box-style, spring-style, and barrier-style terminals and are also available as snap-on auxiliary terminal strips and interposing terminals that can be mounted separately and connected to a connector-style carrier by an I/O cable.

|                               | IC200CHS003                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | IC200CHS011                                                                                                 | IC200CHS012                                                                                                                   | IC200CHS014                                                                                                  | IC200CHS015                                                                                                  |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| Product Name                  | VersaMax I/O Carrier, VersaMax I/O Carrier, Connector Style. Interposing Barrier A connecting cable Style (Requires IC200CBL1xxx) and IC200CHS003 base interposing base (IC200CHS011, and connecting CHS012, CHS014, CHS015, cable IC200CBL1xxx) IC200CHS1xx or IC200CHS2xx) are required. This carrier can be used with all VersaMax I/O modules EXCEPT the following, due to their high isolation requirements: IC200MDL144 Input 240 VAC 4 Point Isolated Module; IC200MDL244 Input 240 VAC 8 Point Isolated Module; IC200MDD850 Mixed 240 VAC Isolated 4 Point / Output Relay 2.0A Isolated 8 Point Module | VersaMax I/O Carrier, Interposing Box Style (Requires IC200CHS003 base and connecting cable IC200CBL1xxx)   | VersaMax I/O Carrier, Interposing Box Thermocouple Compensation (Requires IC200CHS003 base and connecting cable IC200CBL1xxx) | VersaMax I/O Carrier, Interposing Spring Clamp (Requires IC200CHS003 base and connecting cable IC200CBL1xxx) | VersaMax I/O Carrier, Interposing Spring Clamp (Requires IC200CHS003 base and connecting cable IC200CBL1xxx) |
| Lifecycle Status              | Active                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Active                                                                                                      | Active                                                                                                                        | Active                                                                                                       | Active                                                                                                       |
| Field Termination Type        | Integrated                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Non-Integrated                                                                                              | Non-Integrated                                                                                                                | Integrated                                                                                                   | Non-Integrated                                                                                               |
| Wiring Termination Style      | Connector                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Barrier                                                                                                     | Box                                                                                                                           | Box-Thermocouple Compensation                                                                                | Spring                                                                                                       |
| Orientation on Module on Base | Vertical                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | N/A                                                                                                         | N/A                                                                                                                           | N/A                                                                                                          | N/A                                                                                                          |
| Dimensions (W x H x D)        | 66.8 mm (2.63 in) x<br>133.4 mm (5.25 in) x<br>70 mm (2.75 in),<br>not including the<br>height of DIN Rail                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 110.5 mm (4.35 in) x<br>105.4 mm (2.63 in) x<br>70 mm (2.75 in),<br>not including the<br>height of DIN Rail | 110.5 mm (4.35 in) x<br>105.4 mm (2.63 in) x<br>70 mm (2.75 in),<br>not including the<br>height of DIN Rail                   | 110.5 mm (4.35 in) x<br>105.4 mm (2.63 in) x<br>70 mm (2.75 in),<br>not including the<br>height of DIN Rail  | 110.5 mm (4.35 in) x<br>105.4 mm (2.63 in) x<br>70 mm (2.75 in),<br>not including the<br>height of DIN Rail  |
| Cables                        | Requires a<br>IC200CBL1xxx cable                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Requires a<br>IC200CBL1xxx cable                                                                            | Requires a<br>IC200CBL1xxx cable                                                                                              | Requires a<br>IC200CBL1xxx cable                                                                             | Requires a<br>IC200CBL1xxx cable                                                                             |