

Discrete Expansion Units



The VersaMax Micro's modular design provides you with remarkable flexibility in a compact control. The versatile Micro PLC can support up to four Expansion Units of any mix of discrete or analog.

	IC200UEX222	IC200UEX212	IC200UEX211	IC200UEX209	IC200UEX210
Product Name	28 point (16) 24 VDC In, (12) 24 VDC Out with ESCP, 24 VDC Powered	28 point (16) 24 VDC In, (12) Relay Out, 24 VDC Powered	28 point (16) 24 VDC In, (12) Relay Out, 120/240 VAC Powered	28 point (16) 120 VAC In, (12) Relay Out (2 outputs at 10 amp and 10 outputs at 2 amp), 120/240 VAC Powered	28 point (16) 24 VDC In, (12) 120 VAC Out, 120/240 VAC Powered
Lifecycle Status	Active	Active	Active	Active	Active
Micro Type Restrictions	N/A	N/A	N/A	N/A	N/A
Number of Discrete Inputs/Outputs	16 In / 12 Out	16 In / 12 Out	16 In / 12 Out	16 In / 12 Out	16 In / 12 Out
Power Voltage	24 VDC	24 VDC	120/240 VAC	120/240 VAC	120/240 VAC
Input Power Supply Rating	5 Watts	8 Watts	26 VA	16 VA	16 VA
24 VDC User Power for Sensors	200 mA	200 mA	200 mA	200 mA	200 mA
Input Device Voltage	24 VDC	24 VDC	24 VDC	120 VAC	120 VAC
Output Control Voltage	24 VDC ESCP, Self Healing, No External Fusing Required	Relay Out	Relay Out	Relay Out (2 at 10 Amps and 10 at 2 Amps)	120 VAC
Relay Maximum Resistive Load Rating	N/A	2 Amps at 24 VDC and 240 VAC	2 Amps at 24 VDC and 240 VAC	2 Amps at 24 VDC and 240 VAC; 10 Amps at 24 VDC and 240 VAC	N/A
Dimensions (WxHxD) mm	150x90x76	150x90x76	150x90x76	150x90x76	150x90x76