



Micro 20, Micro 40 and Micro 64 Port 2 Communication Options

The VersaMax Micro 20, Micro 40 and Micro 64 Port 2 is modular by design and enables the user to select a wide range of communications options. The user can select RS-232, RS-485, Ethernet or USB. The RS-232 and RS-485 also come with two analog input channels (0 to 10 VDC, 10 bit). Port 2 also supports Memory Module Board that enables the user to download logic and settings without a PC.

	IC200UEM001	IC200USB001	IC200USB002	IC200UUB001
Product Name	Ethernet module	RS-232 option board with (2) 0 -10 VDC analog in	RS-485 option board with (2) 0 -10 VDC analog in	USB option board (no analog option)
Lifecycle Status	Active	Active	Active	Active
Micro Type Restrictions	Micro 20, 40, 64 Support Only	Micro 20, 40, 64 Support Only	Micro 20, 40, 64 Support Only	Micro 20, 40, 64 Support Only
Connection Type	10/100Mbps port supporting RJ45 connection	RS-232 (RJ-45)	RS-485 (RJ-45)	USB (Slave Only) version 2.0, Straight B type
Protocol Supported	SRTP and Modbus TCP (server)	SNP, SNP Master, SNP X, Modbus Master, Modbus Slave, Serial Read and Write	SNP, SNP Master, SNP X, Modbus Master, Modbus Slave, Serial Read and Write	SNP, SNP X, Modbus Slave, Serial Read
Analog Support on Communications Module	No Analog Support	Two Analog Inputs. 0 to 10 VDC (10 bits)	Two Analog Inputs. 0 to 10 VDC (10 bits)	No Analog Support
Memory Module Board Support	Yes	Yes	Yes	Yes
Programming Support	Yes, SRTP only	Yes	Yes	Yes
Programming Software	Proficy Machine Edition Logic Developer 5.0, Service Pack 3, Hotfix	Proficy Machine Edition Logic Developer 5.0, Service Pack 3, Hotfix	Proficy Machine Edition Logic Developer 5.0, Service Pack 3, Hotfix	Proficy Machine Edition Logic Developer 5.0, Service Pack 3, Hotfix