

Accessories/Chimes

a

Overview

Conceals signal and protects against tampering & pilferage.
Grey painted finish.

b

c

d

e

f

g

h

i


index

Yard Hood

Model 1995

Ordering Information

Cat. No.	Usage	Dimensions inches (mm)			
		A	B	C	D
1995	340, 340-A, 435, 870 Series	15 (381)	8 1/4 (209)	10 7/8 (276)	6 (152)




Overview

Attractive, high-quality surface mounted chime for heavy-duty commercial and industrial use.

Heavy-duty construction throughout. No exposed terminals. Underdome construction. Built-in resonator. Convenient Adaptaplate mounting. Plastic tipped stainless steel striker. Special hanger for easy mounting. Tamper-proof cover screw. Requires no lubrication. Can be pulsed as rapidly as 10 pulses/sec. AC; 14 pulses/sec. DC. Low current drain. Satin aluminum finish.

Installation and Mounting

Mounts on any plaster cover with mounting holes on 2-3/4" centers; on any single gang opening; or directly on any 3-1/4", 3-1/2" and 4" octagon box and 4" square box. Also mounts directly on any wall surface.

Single-Stroke
Industrial Chime

Models 338 and 339

Standard Features

- AC or DC
- CSA certified

Applications

Timing, scheduling, paging applications requiring a pleasant note with middle range decibel rating: offices, stores, etc.

Ordering Information

Cat. No.	Volts	Amps	VA	DC Coil Res. (Ohms)	dB at 10' (3M)
338-G5	24 VAC	0.5	12	10	81
338-N5	120 VAC	0.1	12	250	81
339-G1	24Vdc	0.3	7.2	73	81

