

# Edwards® 338 & 339 Series Single-Stroke Chimes



## Features

- AC or DC models
- No exposed terminals
- Tamper-proof cover screw
- Plastic tipped stainless steel striker
- Satin aluminum finish

## Description

The Edwards 338 & 339 are surface mount AC or DC single stroke chimes. The chimes are high quality units intended for heavy-duty commercial and industrial use. The chimes require no lubrication.

## Agency Approvals

- UL Listed

## Specifications

- Can be pulsed up to 10 pulses/second
- Low current drain
- Underdome construction

## Installation

The chimes come complete with an AdaptaPlate® mounting plate. The AdaptaPlate mounts on any plaster cover with mounting holes on 2 3/4" (70mm) centers, on any single gang opening, on any 3 1/4" (83mm), 3 1/2" (89mm), or 4" (102mm) octagon or square box. Also mounts directly on any wall surface. For flush mounting use Cat. No. 512-A grille (page 5-8) and P-029522 back box.

## Applications

For paging and scheduling applications requiring a pleasant note with middle range decibel rating. Ideal for offices and stores.

Cat. No.	Volts	Amps	V A	dB at 10 ft
<b>338-G5</b>	24V AC 50/60 Hz	.5	12	81
<b>338-N5</b>	120V AC 50/60 Hz	.1	12	81
<b>339-E1</b>	12V DC	0.6	7.2	81
<b>339-G1</b>	24V DC	.3	7.2	81
<b>339-P1</b>	125V DC	.06	7.5	81

