

FIBERGLASS

300 lbs. TYPE IA
load capacity*

PLATFORM LADDER FP1500 SERIES



FP1504

**IMPROVED
PLATFORM
DESIGN!**

Gapless and slimmer
for improved storage.

SHOX

SHOX™ - superior
impact absorption

Da Boot™
Patent #7,000,731 B2

Gapless
slip-resistant
platform

Top rail
guard

Double-rivet step
construction



MODEL	HT. TO PLATFORM	STEP SIZE	BOTTOM WIDTH	APPROX. SPREAD	APPROX. WT. (LBS)	APPROX. CUBES
FP1503	2' 10"	3"	23 3/16"	34 1/4"	19	3.9'
FP1504	3' 9"	3"	24 13/16"	39 7/8"	23	5.2'
FP1505	4' 9"	3"	26 3/16"	45 3/4"	25	6.5'
FP1506	5' 8"	3"	27 3/4"	52"	28	7.6'
FP1508	7' 7"	3"	30 7/8"	63 3/4"	41	10'
FP1510	9' 6"	3"	33 13/16"	75 5/8"	57	12.9'
FP1512	11' 5"	3"	36 13/16"	86 5/8"	68	15.4'



ANSI
Meets or exceeds requirements
of American National Standards Institute
ANSI A14.5



FIBERGLASS

375 lbs. TYPE IAA
load capacity*

STEP-TO-STRAIGHT LADDER FC1200 SERIES



FC1206

Hinging
mechanism

Standard
pole grip

Utility-style
safety shoes

Double-rivet
step construction

Runglock



MODEL	LADDER SIZE	MAX. EXT. LENGTH	FLARED SECTION MIN. O.D.	FLARED SECTION MAX. O.D.
FC1206	6'	9'	17 7/8"	23 5/8"
FC1207	7'	11'	17 7/8"	24 5/8"
FC1208	8'	13'	17 7/8"	25 5/8"

Table
continued
below...

MODEL	PARALLEL SECTION O.D.	APPROX. WT. (LBS)	APPROX. CUBES
FC1206	14 5/8"	33	6.8'
FC1207	14 5/8"	36	8.4'
FC1208	14 5/8"	41	9.8'



O.D. denotes outside dimension