

FLEXIBLE COPPER BRAID

(Continued)

TYPE B



D-46

CATALOG NUMBER	NUMBER OF BRAIDS IN FERRULES	C	D	E	K	L	N	T	APPROXIMATE AMPERE RATING	
									INDOOR	OUTDOOR
B2D12 †	2	.94	2.50	1.25	.44	12	.62	.25	380	455
B2D12N** †			3.00	1.75	.56	12	.62			
B2E12		1.62	3.00	1.50	.44	12	.75	.25	530	635
B2E12N**			3.00	1.75	.56	12	.62			
B2F12		1.38	3.00	1.50	.44	12	.75	.38	600	720
B2F12N**			3.00	1.75	.56	12	.62			
B2G12		1.50	3.00	1.50	.44	12	.75	.50	700	840
B2G12N**			3.00	1.75	.56	12	.62			
B3D12 †	3	1.19	2.50	1.25	.44	12	.62	.25	470	560
B3D12N** †			3.00	1.75	.56	12	.62			
B3E12		1.64	3.00	1.50	.44	12	.75	.31	700	840
B3E12N**			3.00	1.75	.56	12	.62			
B3F12		1.44	3.00	1.50	.44	12	.75	.56	820	980
B3F12N**			3.00	1.75	.56	12	.62			
B3G12		1.69	3.00	1.50	.44	12	.75	.69	960	1150
B3G12N**			3.00	1.75	.56	12	.62			
B4D12	4	1.19	2.50	1.25	.44	12	.62	.32	600	720
B4D12N**			3.00	1.75	.56	12	.62			
B4E12		1.64	3.00	1.50	.44	12	.75	.36	850	1020
B4E12N**			3.00	1.75	.56	12	.62			
B4F12		1.50	3.00	1.50	.44	12	.75	.78	1000	1200
B4F12N**			3.00	1.75	.56	12	.62			
B4G12		1.69	3.00	1.50	.44	12	.75	.94	1200	1440
B4G12N**			3.00	1.75	.56	12	.62			

* This rating may vary with ambient conditions, orientation of the braid and other service conditions.
 ** Tongue drilled per (2) hole NEMA standard.

Note: All sizes are listed to UL467 and specific sizes (†) are certified to CSA C22.2, No. 41 Grounding and Bonding Equipment Standards. Equivalent sizes may be designated by suffix letters representing variations in length, mounting configurations, pad size and finish. Contact factory for details.

TYPE B



FLEXIBLE COPPER BRAID

Flexible copper braid jumpers designed to take up linear expansion and contraction, compensate for misalignment and absorb vibratory movement of electrical equipment and devices.

Made of flat extra flexible, tinned, pure copper braid, with unplated, seamless, pure copper ferrules formed into a rectangular shape on each end.

Last two numbers in catalog number indicate total length of braid in inches (e.g., BD12N or BD12 is 12" long braid jumper).

Other lengths, plating and drilling are available. Refer to factory.



D-45



CATALOG NUMBER	NUMBER OF BRAIDS IN FERRULES	C	D	E	K	L	N	T	APPROXIMATE AMPERE RATING	
									INDOOR	OUTDOOR
BD12 †	1	.94	2.50	1.25	.44	12	.62	.13	190	225
BD12N** †										
BD18 †										
BD18N** †										
BD24 †										
BD24N** †										
BE12 †	1	1.50	3.00	1.50	.44	12	.75	.17	340	405
BE12N** †										
BE18 †										
BE18N** †										
BE24 †										
BE24N** †										
BF12 †	1	1.19	3.00	1.50	.44	12	.75	.25	360	430
BF12N** †										
BF18 †										
BF18N** †										
BF24 †										
BF24N** †										
BG12	1	1.50	3.00	1.50	.44	12	.75	.25	415	495
BG12N**										
BG18										
BG18N**										
BG24										
BG24N**										

* This rating may vary with ambient conditions, orientation of the braid and other service conditions.

** Tongue drilled per (2) hole NEMA standard.

Note: All sizes are listed to UL467 and specific sizes (†) are certified to CSA C22.2, No. 41 Grounding and Bonding Equipment Standards. Equivalent sizes may be designated by suffix letters representing variations in length, mounting configurations, pad size and finish. Contact factory for details.