



BIG DAWG™ INCH POUND TORQUE WRENCHES—FIXED HEAD

- 13% smaller head for access in tight work areas.
- 40-200 in./lb thru 100-1000 in./lb.
- 5.7-23.7 Nm thru 17.3-119 Nm.
- Packaged in blow molded plastic box for protection and easy storage.
- Calibrated $\pm 3\%$ of torque reading clockwise and $\pm 6\%$ counterclockwise at 20% to 100% of full scale.
- Certified wrenches to $\pm 2\%$ one direction are available upon request.

Product ID No.	Torque Range		Graduations		Drive Size	Length	Weight lbs.	Box No.
	in./lbs.	Nm	in./lbs.	Nm				
6061F	40-200	5.7-23.7	1	.11	1/4"	11-3/8"	1.65	6006PB
6063F	40-200	5.7-23.7	1	.11	3/8"	11-3/8"	1.96	6006PB
6065F	100-1000	17.3-119.0	5	.56	3/8"	16-1/4"	2.43	6003PB

ANSI Spec.: B107.14M

ISO 6789



BIG DAWG™ FOOT POUND TORQUE WRENCHES—FIXED HEAD

- 13% smaller head for access in tight work areas.
- 10-80 ft/lb thru 90-600 ft/lb
- 21-116 Nm thru 142-834 Nm
- Packaged in blow molded plastic box for protection and easy storage.
- Calibrated $\pm 3\%$ of torque reading clockwise and $\pm 6\%$ counterclockwise at 20% to 100% of full scale.
- Certified wrenches to $\pm 2\%$ one direction are available upon request.

Product ID No.	Torque Range		Graduations		Drive Size	Length	Weight lbs.	Box No.
	ft./lbs.	Nm	ft./lbs.	Nm				
6005F	10-80	21-116	.5	.68	3/8"	16-3/16"	1.79	6003PB
6015F	30-150	47-210	1	1.36	1/2"	20-5/16"	3.79	6004PB
6013F	50-250	75-345	1	1.36	1/2"	25-15/16"	4.50	6005PB
6017B	90-600	142-834	2	1.7	3/4"	41-1/4"	11.20	6007PB

*(Products with "F" suffix only)

ANSI Spec.: B107.14M

ISO 6789



BIG DAWG™ INCH POUND TORQUE WRENCHES—RATCHET HEAD

- 45 tooth gear/floating pawl design for small 6.8° arc swing.
- 13% smaller head for access in tight work areas.
- Reversing lever designed for quick, one hand operation.
- 40-200 in./lb thru 600-3000 in./lb
- 5.7-23.7 Nm thru 73.5-345 Nm.
- Packaged in blow molded plastic box for protection and easy storage.
- Calibrated $\pm 3\%$ of torque reading clockwise and $\pm 6\%$ counterclockwise at 20% to 100% of full scale.
- Certified wrenches to $\pm 2\%$ one direction are available upon request.

Product ID No.	Torque Range		Graduations		Drive Size	Length	Weight lbs.	Box No.
	in./lbs.	Nm	in./lbs.	Nm				
6062F	40-200	5.7-23.7	1	.11	1/4"	11-3/8"	1.86	6006PB
6064F	40-200	5.7-23.7	1	.11	3/8"	11-3/8"	1.86	6006PB
6066F	100-1000	17.3-119.0	5	.56	3/8"	16-1/2"	4.32	6003PB
6068F	300-1800	39.6-209	5	.56	1/2"	20-3/4"	5.01	6004PB
6072F	600-3000	73.5-345	5	.56	1/2"	26-1/4"	5.75	6004PB

ANSI Spec.: B107.14M

ISO 6789



BIG DAWG™ FOOT POUND TORQUE WRENCHES—RATCHET HEAD

- 45 tooth gear/floating pawl design for small 6.8° arc swing.
- 13% smaller head for access in tight work areas.
- Reversing lever designed for quick, one hand operation.
- 10-80 ft/lb thru 140-700 ft/lb
- 21-116 Nm thru 217-976 Nm
- Packaged in blow molded plastic box for protection and easy storage.
- Calibrated $\pm 3\%$ of torque reading clockwise and $\pm 6\%$ counterclockwise at 20% to 100% of full scale.
- Certified wrenches to $\pm 2\%$ one direction are available upon request.

Product ID No.	Torque Range		Graduations		Drive Size	Length	Weight lbs.	Box No.
	ft./lbs.	Nm	ft./lbs.	Nm				
6006F	10-80	21-116	.5	.68	3/8"	16-7/16"	2.00	6003PB
6012F	20-100	34-142	.5	.68	3/8"	16-7/16"	2.40	6003PB
6008F	10-80	21-116	.5	.68	1/2"	16-7/16"	2.00	6003PB
6016F†	30-150	47-210	1	1.36	1/2"	20-3/4"	3.97	6004PB
6014F	50-250	75-345	1	1.36	1/2"	26-1/4"	4.68	6005PB
6018AB	60-300	102-428	2	1.7	3/4"	32-11/16"	9.70	6007PB
6020AB	90-600	142-834	2	1.7	3/4"	41-1/2"	11.60	6007PB
6022B†	140-700	217-976	2	1.7	1"	48"	14.50	6007PB

*(Products with "F" suffix only)

† Secondary Scale in Newton Meters

‡ Meets Ergonomic Criteria

ANSI Spec.: B107.14M

ISO 6789