



Terminal blocks - CLIPLINE complete

2.5 mm² PT... push-in connection terminal blocks


Feed-through, multi-conductor, and multi-level terminal blocks and ground terminals

Notes:

1) For additional accessories and technical data, see page 110.



30 A, double-level terminal block with PE foot



24 A, double-level terminal block, 3 connections per level



Technical data¹⁾

Dimensions	[mm]
Max. electrical data	
Max. bridge current	[A]
Rated data	
Rated voltage	[V]
Nominal current / cross section	[A] / [mm²]

Width	Length	Height
5.2	68	47.5 (NS 35/7,5)
I _{max} [A]	U _{max} [V]	max. Ø [mm²] AWG (UL)
30	500	0.14 - 4 24-12
20 (FBS) / 17.5 (FBSR)		
IEC	UL / CUL	CSA Ex
500	300	300 -
24 / 2.5	20 / -	20 / - -

Ordering data

Description	Color
Terminal block	gray
upper level blue	gray
upper level blue	gray
With potential distribution	gray
Ground terminal	green-yellow

Type	Order No.	Pcs. / Pkt.
PTTB 2,5-PE/L	① 3210978	50
PTTB 2,5-PE/N	① 3210981	50
PTTB 2,5-L/N	② 3210994	50

Accessories¹⁾

Cover, width 2.2 mm	gray
---------------------	------

D-PTTB 2,5	3211634	50
------------	---------	----

Technical data¹⁾

Width	Length	Height
5.2	111.8	55 (NS 35/7,5)
I _{max} [A]	U _{max} [V]	max. Ø [mm²] AWG (UL)
24	500	0.14 - 4 -
20 (FBS) / 17.5 (FBSR)		
IEC	UL / CUL	CSA Ex
500	-	- -
22 / 2.5	-	- -

Ordering data

Type	Order No.	Pcs. / Pkt.
PTTBS 2,5-TWIN	① 3210600	50
PTTBS 2,5-TWIN BU	① 3210601	50
PTTBS 2,5-TWIN-PV	② 3210603	50
PTTBS 2,5-TWIN-PE	③ 3210602	50

Accessories¹⁾



D-PTTBS 2,5-TWIN	3210608	50
------------------	---------	----

Feed-through, multi-conductor, and multi-level terminal blocks and ground terminals


Notes:

1) For additional accessories and technical data, see page 110.

For information on installation and using accessories for Ex applications, see page 602.



24 A, double-level terminal block, 4 connections per level



24 A, multi-level terminal block



Ex: Ex I MEx
SEV13ATEX0159U / IECEx SEV13.0005U

Technical data¹⁾

Dimensions	[mm]
Max. electrical data	
Max. bridge current	[A]
Rated data	
Rated voltage	[V]
Nominal current / cross section	[A] / [mm²]

Width	Length	Height
5.2	115.2	55 (NS 35/7,5)
I _{max} [A]	U _{max} [V]	max. Ø [mm²] AWG (UL)
24	500	0.14 - 4 -
20 (FBS) / 17.5 (FBSR)		
IEC	UL / CUL	CSA Ex
500	-	- -
22 / 2.5	-	- -

Ordering data

Description	Color
Terminal block	gray
blue	blue
With potential distribution	gray
Ground terminal	green-yellow

Type	Order No.	Pcs. / Pkt.
PTTBS 2,5-QUATTRO	① 3210609	50
PTTBS 2,5-QUATTRO BU	① 3210610	50
PTTBS 2,5-QUATTRO-PV	② 3210612	50
PTTBS 2,5-QUATTRO-PE	③ 3210611	50

Accessories¹⁾

D-PTTBS 2,5-QUATTRO	3210613	50
---------------------	---------	----

Technical data¹⁾

Width	Length	Height
5.2	102	58 (NS 35/7,5)
I _{max} [A]	U _{max} [V]	max. Ø [mm²] AWG (UL)
24	500	0.14 - 4 26-12
20 (FBS) / 17.5 (FBSR)		
IEC	UL / CUL	CSA Ex
500	300	300 440
20 / 2.5	20 / -	20 / - 17 / 2.5

Ordering data

Type	Order No.	Pcs. / Pkt.
PT 2,5-3L	① 3210499	50
PT 2,5-3L BU	① 3210509	50
PT 2,5-3PV	② 3210512	50
PT 2,5-3PE	③ 3210525	50

Accessories¹⁾

D-PT 2,5-3L	3211647	50
-------------	---------	----