


1.5 mm² ST... spring-cage connection terminal blocks

Feed-through, multi-conductor, and multi-level terminal blocks and ground terminals

Notes:
 1) For additional accessories and technical data, see page 166.
 For information on installation and using accessories for Ex applications, see page 602.



17.5 A, feed-through terminal block



Ex: KEMA 01ATEX2129 U / IECEx KEM 06.0043U

Technical data¹⁾

Width	Length	Height		
4.2	48.5	36.5 (NS 35/7,5)		
I _{max.} [A]	U _{max.} [V]	max. Ø [mm ²]	AWG (UL)	
17.5	500	0.08 - 1.5	26-14	
17.5				
IEC	UL / CUL	CSA	Ex	
500	300	300	440	
Nominal current / cross section	[A] / [mm ²]			
17.5 / 1.5	15 / - 15 / - 17.5 / 1.5			

Ordering data

Type	Order No.	Pcs. / Pkt.
ST 1,5	① 3031076	50
ST 1,5 BU	① 3031089	50
ST 1,5-PE	② 3031513	50


Accessories¹⁾

D-ST 2,5	Order No.	Pcs. / Pkt.
D-ST 2,5	3030417	50

Dimensions	[mm]
Max. electrical data	
Max. bridge current	[A]
Rated data	
Rated voltage	[V]
Nominal current / cross section	[A] / [mm ²]

Description	Color
Terminal block	gray blue
Ground terminal	green-yellow

Cover, width 2.2 mm	Color
Cover, width 2.2 mm	gray



17.5 A, feed-through terminal block, 3 connections



Ex: KEMA 01ATEX2129 U / IECEx KEM 06.0043U

Technical data¹⁾

Width	Length	Height		
4.2	60.5	36.5 (NS 35/7,5)		
I _{max.} [A]	U _{max.} [V]	max. Ø [mm ²]	AWG (UL)	
17.5	500	0.08 - 1.5	26-14	
17.5				
IEC	UL / CUL	CSA	Ex	
500	300	300	440	
Nominal current / cross section	[A] / [mm ²]			
17.5 / 1.5	15 / - 15 / - 17.5 / 1.5			

Ordering data


Type	Order No.	Pcs. / Pkt.
ST 1,5-TWIN	① 3031128	50
ST 1,5-TWIN BU	① 3031131	50
ST 1,5-TWIN-PE	② 3031144	50

Accessories¹⁾

D-ST 2,5-TWIN	Order No.	Pcs. / Pkt.
D-ST 2,5-TWIN	3030488	50

Feed-through, multi-conductor, and multi-level terminal blocks and ground terminals

Notes:
 1) For additional accessories and technical data, see page 166.
 For information on installation and using accessories for Ex applications, see page 602.



17.5 A, feed-through terminal block, 4 connections



Ex: KEMA 01ATEX2129 U / IECEx KEM 06.0043U

Technical data¹⁾

Width	Length	Height		
4.2	72	36.5 (NS 35/7,5)		
I _{max.} [A]	U _{max.} [V]	max. Ø [mm ²]	AWG (UL)	
17.5	500	0.08 - 1.5	26-14	
17.5				
IEC	UL / CUL	CSA	Ex	
500	300	300	440	
Nominal current / cross section	[A] / [mm ²]			
17.5 / 1.5	15 / - 15 / - 17.5 / 1.5			

Ordering data

Type	Order No.	Pcs. / Pkt.
ST 1,5-QUATTRO	① 3031186	50
ST 1,5-QUATTRO BU	① 3031199	50
ST 1,5-QUATTRO-PE	② 3031209	50



Accessories¹⁾

D-ST 2,5-QUATTRO	Order No.	Pcs. / Pkt.
D-ST 2,5-QUATTRO	3030514	50

Dimensions	[mm]
Max. electrical data	
Max. bridge current	[A]
Rated data	
Rated voltage	[V]
Nominal current / cross section	[A] / [mm ²]

Description	Color
Terminal block	gray gray blue
Ground terminal	green-yellow

Cover, width 2.2 mm	Color
Cover, width 2.2 mm	gray



17.5 A, feed-through terminal block, 4 connections, with interrupted current bar



Technical data¹⁾

Width	Length	Height		
4.2	72	36.5 (NS 35/7,5)		
I _{max.} [A]	U _{max.} [V]	max. Ø [mm ²]	AWG (UL)	
17.5	500	0.08 - 1.5	26-14	
17.5				
IEC	UL / CUL	CSA	Ex	
500	300	-	-	
Nominal current / cross section	[A] / [mm ²]			
17.5 / 1.5	15 / - - - -			

Ordering data

Type	Order No.	Pcs. / Pkt.
ST 1,5-QUATTRO-U	① 3038600	50

Accessories¹⁾

D-ST 2,5-QUATTRO	Order No.	Pcs. / Pkt.
D-ST 2,5-QUATTRO	3030514	50