


Feed-through terminal blocks and ground terminals

Notes:

¹⁾ For additional accessories and technical data, see page 60.

For information on installation and using accessories for Ex applications, see page 602.



76 A, feed-through terminal block and ground terminal



Ex: KEMA 04ATEX2048 U / IECEx KEM 06.0027U

Technical data¹⁾

Width	Length	Height	
10.2	47.7	47.5 (NS 35/7,5)	
I _{max} [A]	U _{max} [V]	max. Ø [mm ²]	AWG (UL)
76	1000	0.5 - 16	20-6
57			
IEC	UL / CUL	CSA	Ex
1000	600	600	690
57 / 10	65 / -	65 / -	54 / 10

Ordering data

Type	Order No.	Pcs. / Pkt.
UT 10	① 3044160	50
UT 10 BU	① 3044188	50
UT 10-PE	② 3044173	50
UT 10-PE/S	② 3215054	50

Accessories¹⁾

D-UT 2,5/10	3047028	50
-------------	---------	----

Dimensions

[mm]

Max. electrical data

Max. bridge current [A]

Rated data

Rated voltage [V]

Nominal current / cross section [A] / [mm²]

Description Color

Terminal block gray

blue

Ground terminal green-yellow

With screw foot green-yellow

Cover, width 2.2 mm gray


Installation terminal blocks

Notes:

¹⁾ For additional accessories and technical data, see page 60.

Assembly instruction:

In order to securely fix the neutral busbar in place, support brackets must be placed at the beginning and end of each terminal strip as well as every 20 cm on longer terminal strips. The corresponding support brackets can be found at phoenixcontact.net/products



57 A, neutral disconnect terminal block



Technical data¹⁾

Width	Length	Height	
10.2	55	47.5 (NS 35/7,5)	
I _{max} [A]	U _{max} [V]	max. Ø [mm ²]	AWG (UL)
57	400	0.5 - 16	-
57			
IEC	UL / CUL	CSA	Ex
400	-	-	-
57 / 10	-	-	-

Ordering data

Type	Order No.	Pcs. / Pkt.
UTN 10	① 3245040	50

Accessories¹⁾

D-UTN 2,5/10	3245079	50
AB-UTN 2,5/10	3245082	50

Dimensions

[mm]

Max. electrical data

Max. bridge current [A]

Rated data

Rated voltage [V]

Nominal current / cross section [A] / [mm²]

Description Color

Terminal block blue

Cover, width 2.2 mm blue

Support bracket blue