

INSULATED SINGLE FERRULES, DIN 46228/4

For Copper Stranded Wire Only


Ferrules are a convenient device used for termination of stranded wires. Ferrules eliminate the risk of fraying single strands and consequential accidental contacts and short circuits. They also protect the wire from damage when using compression screw, spring, or split-bolt type connectors.



Polypropylene Insulated Ferrules

Rated at 600V Max, 105°C

Colour DIN	Part-No.	AWG	Size mm ²	d1	d2	l1	l2	s1	s2	Packing Unit	Approved Tool V Series	CRIMP TOOLS		
												RAT-FER	SPR-FER	RAT-FER2
	FER-22-8D	22	0.50	1.00	2.60	14.00	8.00	0.15	0.25	500	V915	•	•	
	FER-22-6D	22	0.50	1.00	2.60	12.00	6.00	0.15	0.25	500	V915	•	•	
	FER-20-8D	20	0.75	1.20	2.80	14.00	8.00	0.15	0.25	500	V915	•	•	
	FER-20-12D	20	0.75	1.20	2.80	18.00	12.00	0.15	0.25	500	V915	•	•	
	FER-18-8D	18	1.00	1.40	3.00	14.00	8.00	0.15	0.25	500	V915	•	•	
	FER-18-12D	18	1.00	1.40	3.00	18.00	12.00	0.15	0.25	500	V915	•	•	
	FER-16-8D	16	1.50	1.70	3.50	14.00	8.00	0.15	0.25	500	V915	•	•	
	FER-16-10D	16	1.50	1.70	3.50	16.00	10.00	0.15	0.25	500	V915	•	•	
	FER-14-8D	14	2.50	2.20	4.20	14.00	8.00	0.15	0.25	500	V915	•	•	
	FER-14-12D	14	2.50	2.20	4.20	18.00	12.00	0.15	0.25	500	V915	•	•	
	FER-12-10D	12	4.00	2.80	4.80	17.00	10.00	0.20	0.30	500	V915	•	•	
	FER-12-12D	12	4.00	2.80	4.80	20.00	12.00	0.20	0.30	500	V915	•	•	
	FER-10-12C	10	6.00	3.50	6.30	20.00	12.00	0.20	0.30	100	V925		•	•
	FER-8-12C	8	10.00	4.50	7.60	22.00	12.00	0.20	0.40	100	V925		•	•



Technical Information

Insertion Funnel is made of Polypropylene and is heatresistant up to 105 Deg. C. Material: E-Copper, Surface electro tinned. Minimum Coating Thickness 3µm. Rated at 600V Max Tolerances: after part 4

See Page E-5 for tools.

FERRULES IN ASSORTMENT BOXES



Assortment Box with Insulated Single Ferrules



Part-No.	AWG	Content			Colour DIN	Approved Tool V Series	CRIMP TOOLS		
		Quantity	mm ²	l2			RAT-FER	SPR-FER	RAT-FER2
FER-PAC111	Type 1	50	0.50	8		V915	•	•	
		100	0.75	8		V915	•	•	
		100	1.00	8		V915	•	•	
		100	1.50	8		V915	•	•	
		50	2.50	8		V915	•	•	

Assortment Box with Non-insulated Ferrules



Part-No.	AWG	Content			Size	Approved Tool V Series	CRIMP TOOLS		
		Quantity	mm ²	l2			RAT-FER	SPR-FER	RAT-FER2
FER-PAC050	Type 2	500	0.50	6	0.50-2.50 mm ²	V915	•	•	
		500	0.75	6		V915	•	•	
		400	1.00	6		V915	•	•	
		300	1.50	7		V915	•	•	
		200	2.50	7		V915	•	•	

See Page E-5 for tools.

For Copper Stranded Wire Only

See Page E-5 for tools.