

### TYPE

# Thin Wall

#### Features

- 2:1 shrink ratio
- UL Recognized and CSA Certified
- Rated for 600 volts
- Convenient disk dispenser

#### Benefits

- Provides a wide range of coverage when used on connectors and cable
- Assures product reliability for insulating and protecting terminations and splices
- Ensures reliability
- Protects tubing from damage and keeps it clean



Catalog Number	Wire Range	Exp. Id.	Rec. Id.	Recovered Wall Thickness	L
24001-B10	26-34	0.046	0.023	0.016	6"
24002-B10	24-30	0.063	0.031	0.017	6"
24003-B10	22-28	0.093	0.046	0.020	6"
24004-B10	20-26	0.125	0.062	0.020	6"
24005-B10	18-22	0.187	0.093	0.020	6"
24006-B10	14-16	0.250	0.125	0.025	6"
24007-B5	10-12	0.312	0.156	0.025	6"
24008-B5	6-8	0.375	0.187	0.025	6"
24009-B5	4-6	0.500	0.250	0.025	6"
24010-B5	2/0-2	0.750	0.375	0.030	6"
24011-B5	4/0-1	1.000	0.500	0.035	6"
24999-B12+	-	-	-	-	-
25001	26-34	0.046	0.023	0.016	96" Disk
25002	24-30	0.063	0.031	0.017	96" Disk
25003	22-28	0.093	0.046	0.020	96" Disk
25004	20-26	0.125	0.062	0.020	96" Disk
25005	18-22	0.187	0.093	0.020	96" Disk
25006	14-16	0.250	0.125	0.025	96" Disk
25007	10-12	0.3112	0.156	0.025	96" Disk
25008	6-8	0.375	0.187	0.025	96" Disk
25009	4-6	0.500	0.250	0.025	96" Disk
25010	2/0-2	0.750	0.375	0.030	96" Disk
25011	4/0-1	1.000	0.500	0.035	96" Disk

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)  
 + 24999-B12 contains 3 ea. 24005, 24006, 24008, 24009  
 UL File E158587