


Cable Ties



TY523MX
Tie body width 0.091 in.



TY524MX
Tie body width 0.140 in.



TY525MX
Tie body width 0.184 in.



TY5272MX
Actual size body width 0.270 in.

The MX Series cable ties are recommended for outdoor use.



ULTRAVIOLET
RESISTANT



Std. Cat. No.	Bulk Cat. No.	Body Width (in./mm)	Length (in./mm)	Max. Wire Bundle Dia. (in./mm)	Military Standard Part No.	Tensile Strength (lb./N)	Std. Pkg.	Bulk Pkg.
Ty-Rap® Nylon 6/6 – Weather-Resistant								
TY523MX	TY23MX	0.09/2.29	3.62/91.95	0.63/16.00	MS3367-4	18/80.07	100	1,000
TY52315MX	TYB2315MX		7.00/177.80	1.50/38.10	–			
TY5232MX	TY232MX		8.00/203.20	2.00/50.80	–			
TY5234MX	TY234MX		14.00/355.60	4.00/101.60	–			
TY524MX	TY24MX	0.14/3.56	5.50/139.70	1.13/28.70	MS3367-5	40/177.90		
TY5242MX	TY242MX		8.19/208.03	2.00/50.80	–			
TY526MX	TY26MX		11.10/281.94	3.00/76.20	–			
TY5244MX	TY244MX		14.50/368.30	4.00/101.60	–			
TY525MX	TY25MX	0.19/4.83	7.31/185.67	1.75/44.45	MS3367-1	50/222.40		
TY5253MX	TY253MX		11.60/294.64	3.00/76.20	MS3367-7			
TY528MX	TY28MX		14.20/360.68	4.00/101.60	MS3367-2			
TY5272MX†	TY272MX†	0.27/6.86	8.75/222.25	2.00/50.80	–	120/533.80	50	500
TY527MX†	TY27MX		13.40/340.36	3.50/88.90	MS3367-3			
TY5275MX	TY275MX		18.00/457.20	5.00/127.00	–			
TY5277MX	TY277MX		24.30/617.22	7.00/177.80	–			
TY529MX	TY29MX*		30.00/762.00	9.00/228.60	MS3367-6			
TY53510MX**	–	0.32/8.13	35.00/889.00	10.00/254.00	–	175/778.40	–	
TY53513MX**	–		45.00/1143.00	13.00/330.20	–			

* For military compliance of weather-resistant black 120 lb. ties, replace suffix X with O (i.e. TY27M-O).

† Not © Listed or Recognized Models or CSA Certified.

**

CSA Certified. Natural 6/6 Nylon Cable Ties are suitable for use in air handling spaces in accordance with rules 12-010 (3), (4) and (5), and 12-020 of the CEC.