





12HD361



600 Vac Heavy-Duty, Fusible, Single-Throw, 277/480–600V—Type 12/3R^①, 4X^④ and 4^⑦

System	Ampere Rating	Fuse Class Provision	Maximum Horsepower Ratings with Time Delay Fuses						Type 12/3R ^① Enclosure Dust-Tight Catalogue Number	Type 4X ^④ and 4 ^⑦ Enclosure Watertight, Catalogue Number
			Single-Phase AC		Three-Phase AC		DC			
			480V	600V	480V	600V	250V	600V		
Two-Pole—480 Vac—600 Vac or Vdc^② (Suitable for Service Entrance Use with a Neutral Kit Installed)										
	30	H	7-1/2	10	—	—	—	15	12HD261 ^①	4HD261 ^④
	60	H	20	25	—	—	—	25	12HD262 ^①	4HD262 ^④
	100	H	30	40	—	—	20	25	12HD263 ^①	4HD263 ^④
	200	H	50	50	—	—	—	50	12HD264 ^①	4HD264 ^④
	400	H	—	—	—	—	50	—	12HD265 ^①	4HD265SS ^④
	400	H	—	—	—	—	50	—	—	4HD265 ^⑦
	600	H	—	—	—	—	—	—	12HD266 ^①	4HD266SS ^④
	600	H	—	—	—	—	—	—	—	4HD266 ^⑦
	800	L	—	—	—	—	—	—	12HD267 ^{①②}	4HD267SS ^④
	800	L	—	—	—	—	—	—	—	4HD267 ^⑦
	1200	L	—	—	—	—	—	—	⑤③	⑤③
Three-Pole—480 Vac—600 Vac, 250 Vdc (Suitable for Service Entrance Use with a Neutral Kit Installed)										
	30	H	7-1/2	10	15	20	—	—	12HD361 ^①	4HD361 ^④
	60	H	20	25	30	50	—	—	12HD362 ^①	4HD362 ^④
	100	H	30	40	60	75	—	—	12HD363 ^①	4HD363 ^④
	200	H	50	50	125	150	—	—	12HD364 ^①	4HD364 ^④
	400	H	—	—	250	350	—	—	12HD365 ^①	4HD365SS ^④
	400	H	—	—	250	350	—	—	—	4HD365 ^⑦
	600	H	—	—	400	500	—	—	12HD366 ^①	4HD366SS ^④
	600	H	—	—	400	500	—	—	—	4HD366 ^⑦
	800	L	—	—	500	500	—	—	12HD367 ^①	4HD367SS ^④
	800	L	—	—	500	500	—	—	—	4HD367 ^⑦
	1200	L	—	—	500	500	—	—	12HD368 ^{①⑤}	4HD368SS ^{④⑤}
	1200	L	—	—	500	500	—	—	—	4HD368 ^{⑤⑦}
Four-Wire (Three Blades, Three Fuses, S/N) 480 Vac—600 Vac, 250 Vdc										
	30	H	7-1/2	10	15	20	—	—	12HD361N ^①	4HD361N ^④
	60	H	20	25	30	50	—	—	12HD362N ^①	4HD362N ^④
	100	H	30	40	60	75	—	—	12HD363N ^①	4HD363N ^④
	200	H	50	50	125	150	—	—	12HD364N ^①	4HD364N ^④
	400	H	—	—	250	350	—	—	12HD365N ^①	4HD365N ^④
	400	H	—	—	250	350	—	—	—	4HD365N ^⑦
	600	H	—	—	400	500	—	—	12HD366N ^①	4HD366N ^④
	600	H	—	—	400	500	—	—	—	4HD366N ^⑦
	800	L	—	—	500	500	—	—	12HD367N ^①	4HD367N ^④
	800	L	—	—	500	500	—	—	—	4HD367N ^⑦
	1200	L	—	—	500	500	—	—	12HD368N ^{①⑤}	⑤③
	1200	L	—	—	500	500	—	—	—	⑤③
Four-Pole—480 Vac—600 Vac, 250 Vdc										
	30	H	20 ^⑤	25 ^⑤	15	20	—	—	12HD461 ^①	4HD461 ^④
	60	H	40 ^⑤	50 ^⑤	30	50	—	—	12HD462 ^①	4HD462 ^④
	100	H	50 ^⑤	50 ^⑤	60	75	—	—	12HD463 ^①	4HD463 ^④
	200	H	—	—	125	150	40	—	12HD464 ^①	4HD464 ^④
	400	H	—	—	250	350	50	—	12HD456 ^①	③
	600	H	—	—	400	500	—	—	12HD466 ^①	③

See NOTES listed on Page 26.