

600 Vac Heavy-Duty, Non-Fusible, Single-Throw, 277/480–600V—Type 12/3R^①, 4X^⑤ and 4^④

		Maximum Horsepower Ratings									
		Single-Phase AC			Three-Phase AC			DC		Type 12/3R Enclosure Dust-Tight Catalogue Number	Type 4X ^⑤ and 4 ^④ Enclosure Watertight, Painted Steel Catalogue Number
System	Ampere Rating	240V	480V	600V	240V	480V	600V	250V	600V		
Two-Pole—480 Vac—600 Vac or Vdc ^②											
	30	3	7-1/2	10	—	—	—	5	15	12HD261NF ^①	4HD261NF ^⑤
	60	10	20	25	—	—	—	10	25	12HD262NF ^①	4HD262NF ^⑤
	100	20	30	40	—	—	—	20	25	12HD263NF ^①	4HD263NF ^⑤
	200	15	50	50	—	—	—	40	50	12HD264NF ^①	4HD264NF ^⑤
	400	—	—	—	—	—	—	50	—	12HD265NF ^①	4HD265NFSS ^⑤
	400	—	—	—	—	—	—	50	—	—	4HD265NF ^④
	600	—	—	—	—	—	—	—	—	12HD266NF ^①	4HD266NFSS ^⑤
	600	—	—	—	—	—	—	—	—	—	4HD266NF ^④
	800	—	—	—	—	—	—	—	—	12HD267NF ^{①②}	4HD267NFSS ^⑤
	800	—	—	—	—	—	—	—	—	—	4HD267NF ^④
	1200	—	—	—	—	—	—	—	—	③	③
Three-Pole—480 Vac—600 Vac, 250 Vdc											
	30	3	7-1/2	10	10	20	30	5	—	12HD361NF ^①	4HD361NF ^⑤
	60	10	20	25	20	50	60	10	—	12HD362NF ^①	4HD362NF ^⑤
	100	20	40	50	40	75	100	20	—	12HD363NF ^①	4HD363NF ^⑤
	200	15	50	50	60	125	150	40	—	12HD364NF ^①	4HD364NF ^⑤
	400	—	—	—	125	250	350	50	—	12HD365NF ^①	4HD365NFSS ^⑤
	400	—	—	—	125	250	350	50	—	—	4HD365NF ^④
	600	—	—	—	200	400	500	—	—	12HD366NF ^①	4HD366NFSS ^⑤
	600	—	—	—	200	400	500	—	—	—	4HD366NF ^④
	800	—	—	—	—	500	500	—	—	12HD367NF ^①	4HD367NFSS ^⑤
	800	—	—	—	—	500	500	—	—	—	4HD367NF ^④
	1200	—	—	—	—	500	500	—	—	12HD368NF ^①	4HD368NFSS ^⑤
	1200	—	—	—	—	500	500	—	—	—	4HD368NF ^④
Four-Pole—480 Vac—600 Vac, 250 Vdc											
	30	10 ^⑤	20 ^⑤	25 ^⑤	10	20	30	5	—	12HD461NF ^①	4HD461NF ^⑤
	60	20 ^⑤	40 ^⑤	50 ^⑤	20	50	60	10	—	12HD462NF ^①	4HD462NF ^⑤
	100	40 ^⑤	50 ^⑤	50 ^⑤	40	75	100	20	—	12HD463NF ^①	4HD463NF ^⑤
	200	50 ^⑤	50 ^⑤	50 ^⑤	60	125	150	40	—	12HD464NF ^①	4HD464NF ^⑤
	400	50 ^⑤	—	—	125	250	350	50	—	①③	—
	600	—	—	—	200	400	500	—	—	①③	—
	800	—	—	—	—	—	—	—	—	①②③	—

Notes

- ① Type 12 enclosures (30–1200A) can be field modified to meet Type 3R rainproof requirements when a factory provided drain hole is opened.
 ② DC rating for 800A switches is 250V.
 ③ Contact Customer Support (1-800-268-3578) for availability of this product.
 ④ Ratings are for two-phase AC.
 ⑤ Type 4X stainless steel enclosure.
 ⑥ Type 4 painted steel enclosure.