



Models

Product #	Volts	Watts	Weight	
			lbs	kg
OACp4008	208	4000	20.0	9.0
OACp8008	208	8000	40.0	18.0
OACp1500	240/208	1500/1125	20.0	9.0
OACp2000	240/208	2000/1500	20.0	9.0
OACp3000	240/208	3000/2250	20.0	9.0
OACp4000	240/208	4000/3000	20.0	9.0
OACp6000	240/208	6000/4500	40.0	18.0
OACp8000	240/208	8000/6000	40.0	18.0
OACp1507	347	1500	26.0	12.0
OACp2007	347	2000	26.0	12.0
OACp3007	347	3000	26.0	12.0
OACp4007	347	4000	26.0	12.0
OACp6007	347	6000	52.0	24.0
OACp8007	347	8000	52.0	24.0
OACp1506	600	1500	26.0	12.0
OACp2006	600	2000	26.0	12.0
OACp3006	600	3000	26.0	12.0
OACp4006	600	4000	26.0	12.0
OACp6006	600	6000	52.0	24.0
OACp8006	600	8000	52.0	24.0

Add "BL" for white, "AM" for almond.

Accessories

Product #	Description		
OACp-T-BAR	Adaptor for T-bar ceilings installations	23 3/4 in. x 23 3/4 in. (602 mm x 602 mm)	1500W to 4000W
OACp-T-BAR2	Adaptor for T-bar ceilings installations	23 3/4 in. x 47 11/16 in. (602 mm x 1211 mm)	6000W to 8000W
OAC-BS1	Surface mounting box		1500W to 4800W
OAC-BS2	Surface mounting box		6000W to 8000W
OAC-DVA	Extruded aluminum front grill		4800W and less
OAC-DVA2	Extruded aluminum front grill		6000W to 8000W
OAC-BSA	Surface mounting box for an aluminum front grill		4800W and less
OAC-BSA2	Surface mounting box for an aluminum front grill		6000W to 8000W

Control Options

Product #	Description
Product no-RT*	24V relay with transformer
Product no-R*	24V relay without transformer
OACp-RT	24V relay with transformer (kit)
OACp-R	24V relay without transformer (kit)
OACp-T	Thermostat (kit)
OACp-DIS20*	Disconnect switch 240V, double-pole, 20A
OACp-DIS40*	Disconnect switch 600V, three-pole, 40A

* Factory installed



OACP series

Commercial Ceiling Heater

For ceiling mounting

The OACP heater is similar to the OAC model but is designed for ceiling mounting when no wall space is available.



apartment building

commercial building

drop ceiling

stairwell

garage

Features

- Color**
 - Standard: white, almond.
 - Optional and custom colors available upon request.
- Finish**
 - Standard: epoxy/polyester powder paint.
- Voltage**
 - 208V, 240V/208V, 277V, 347V, 480V, 600V, 1-phase.
- Construction**
 - 18-gauge steel louvres; grille with rounded corners*.
 - High-limit temperature control with automatic reset.
- Fan**
 - Factory-lubricated motor (open and ventilated).
 - 160 cfm fan (1.5 to 4.8 kW; 55.5 dBA),
 - 2 X 160 cfm fan (6 to 8 kW; 58.5 dBA).
 - Fan delay purges heater of residual heat.
 - (Any remote thermostat or relay must be connected to the heater control terminal block.)
- Heating element**
 - Durable tubular heating element with fins.
- Control**
 - 240V control (standard with contactor when needed).
 - Available with 24V relay, with or without transformer.
- Installation**
 - Standard 60 °C (140 °F) wiring is sufficient.
 - Adaptor for surface mounting available.
 - Adaptor for T-Bar ceiling available.
 - Maximum recommended installation height: 10 ft. (3 m).
 - Minimum clearance from adjacent walls: 10 in. (25.4 cm).
- Warranty**
 - 1-year warranty against defects.

* Grilles with rounded corners may be installed on existing units.