

600V AC Heavy Duty Double Throw, Fusible, Non-Fusible

Fusible

Amperes Main and Standby	Fuse Class Provision	Type 1 Enclosure Indoor	Type 3R Enclosure Rainproof	Type 12 Enclosure Industrial Dust-tight	Type 4X Enclosure Corrosion Resistant Stainless Steel	Maximum Horsepower Ratings with Time Delay Fuses				
		Catalogue Number	Catalogue Number	Catalogue Number	Catalogue Number	1-Phase AC 480V	3-Phase AC 600V	DC 480V	DC 600V	DC 250V

3-Pole – 600V AC – 250V DC

30	H	1DT361	—	—	—	7-1/2	10	15	20	5
60	H	1DT362	—	—	—	20	25	30	50	10
100	H	1DT363	—	—	—	30	40	60	75	20
200	H	1DT364	3DT364	—	—	50	50	125	150	40
400	T	1DT365	—	—	—	—	—	250	350	50

Non-Fusible^②

Amperes Main and Standby	Type 1 Enclosure Indoor	Type 3R Enclosure Rainproof	Type 12 Enclosure Industrial Dust-tight	Type 4X Enclosure Corrosion Resistant Stainless Steel	Maximum Horsepower Ratings					
	Catalogue Number	Catalogue Number	Catalogue Number	Catalogue Number	1-Phase AC 480V	3-Phase AC 600V	DC 480V	DC 600V	DC 250V	DC 600V

2-Pole – 600V AC – 250V DC^②

30	1DT261NF	—	—	—	7-1/2	10	—	—	5	—
60	1DT262NF	—	—	—	20	25	—	—	10	—
100	1DT263NF	—	—	—	30	40	—	—	20	—
200	1DT264NF ^③	3DT264NF ^③	—	—	50	50	—	—	40	50
400	1DT265NF	3DT265NF	—	—	—	—	250	350	50	—
600	1DT266NF	3DT266NF	—	—	—	—	250	350	50	—

3-Pole – 600V AC – 250V DC^②

30	1DT361NF	3DT361NF	12DT361NF ^①	4DT361NF	7-1/2	10	20	20	5	—
60	1DT362NF	3DT362NF	12DT362NF ^①	4DT362NF	20	25	50	50	10	—
100	1DT363NF	3DT363NF	12DT363NF ^①	4DT363NF	30	40	75	100	20	—
200	1DT364NF	3DT364NF	12DT364NF ^①	4DT364NF	50	50	125	150	40	—
400	1DT365NF	3DT365NF	12DT365NF	—	—	—	250	350	50	—
600	1DT366NF	3DT366NF	—	—	—	—	250	350	50	—
800	1DT367NF	3DT367NF	—	—	—	—	250	350	50	—

4-Pole – 600V AC – 250V DC^②

30	—	3DT461NF	—	—	7-1/2	10	20	20	5	—
60	—	3DT462NF	—	—	20	25	20	60	10	—
100	—	3DT463NF	—	—	30	40	75	100	20	—
200	1DT464NF	3DT464NF	—	—	50	50	125	150	40	—
400	1DT465NF	—	—	—	—	—	250	350	50	—
600	1DT466NF	—	—	—	—	—	250	350	50	—
800	1DT467NF	—	—	—	—	—	—	—	—	—

6-Pole – 600V AC – 250V DC^②

30	—	3DT661NF	—	—	7-1/2	10	15	20	5	—
60	—	3DT662NF	—	—	20	25	50	60	10	—
100	—	3DT663NF	—	—	30	40	75	100	20	—

① Type 12 enclosures (30-200 amperes) can be field modified to meet Type 3R rainproof requirements when a factory provided drain hole is opened.

② **WARNING!** Non-fusible switch is not approved for service entrance.

③ Rated 600V AC – 600V DC @ 50 HP.

NOTES:

For 800A non-fusible DT with **NEUTRAL**, must be factory installed, for 600V order as 1DT367NF-N or 3DT367NF-N for EEMAC 3R. Dimensions same as 4 pole switch.

For 'J' Fusing on 600V DT, 30, 60, 100A not available.
For 200A reposition loadside fuse base to accept J Fuse.
For 400A order DT400JK adapter kit.