

T822 Rectangular Thermostat with Mercury Bulb



Models

Product #	Color	Range	Description
T822D2550	White	50 °F to 86 °F	Mercury bulb adjustable anticipator (control up to 5 relays)
T822D1024	Beige		

OTL101F Line Voltage Thermostat



Models

Product #	Power	Range	Description
OTL101F	19A at 277V 22A at 240V	40 °F to 75 °F	Single-pole, single-throw, white
OTL102F			Double-pole, single-throw, white

F29 Universal Guard



Model

Product #	Description
F29-0143	Protects both line and low voltage thermostats against vandalism, damage and unauthorized temperature settings

RT850 Electronic Triac Relay



The all in one solution. Silent operation, optimum regulation when combined with a pulse proportional thermostat. Integrated or nonintegrated 24V transformer as well as indicator light to see at a glance whether the triac relay is on. Can control power levels of 23A and 208V/240V/277V/347V.

Models

Product #	Voltage 60 Hz	Resistive charge (A)	Input signal
Without transformer (pulsing)			
RT850	120/208/240	23	24Vca and 4 to 32Vcc
	277	23	
With transformer			
RT850T-240	208/240	23	24Vca
RT850T-277	277	23	24Vca

RT840 Conventional On/Off Relay



Models

Product #	Voltage 60 Hz	Resistive charge (A)
Without transformer		
RC840	120	22
	208/240	22
	277	19
With transformer		
24A05A-1	120	25
RC840T-240	208/240	22
RC840T-277	277	19