Eaton Bussmann series FWX high speed fuse

FWX-5A14F

UPC:051712795548

Dimensions:

Height: 14 MMLength: 51 MMWidth: 14 MM

Weight: 22.4 G

Warranties:

· Not Applicable

Specifications:

• Type: High speed fuse

 Application: protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters

• Voltage Rating: 600V

• Voltage Rating Numeric: 250 V

• Amperage Rating: 5A

• Amperage Rating Numeric: 5 A

 Interrupt Rating: 200 kAIC Vac, 50 kAIC at 250 Vdc

• Connection: Ferrule end X ferrule end

• Construction Size: 14 x 51 mm

• Packaging Type: Standard

• Breaking Capacity: 200 A

Clearing (I2T): Clearing at 250V: 13Frequency Rating Maximum: 62 HZ

• Frequency Rating Minimum: 45 HZ

• Fuse Shape: cylindrical

• Fuse Indicator: Non Indicating

• Pre Arc (I2T): 1.6

• Release Characteristic: Other

• Utilization category: aR (accompanied

semiconductor protection)



Voltage Type: AC/DCWatt Losses: 1.3WWith Striker: No

Supporting documents:

Product Catalog

Certifications:

• UL Recognized

Product compliance:

CE Marked

© 2016 Eaton. All rights reserved.