Eaton Bussmann series FWJ high speed fuse

FWJ-20A14F

UPC:051712796101

Dimensions:

Height: 14 MMLength: 67 MMWidth: 14 MM

Weight:21.2 G

Warranties:

· Not Applicable

Specifications:

• Type: High speed fuse

 Application: protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters

 Voltage Rating: 700 Vac (UL), 690 Vac (IEC), 500 Vdc (2-100A), 500 Vac

• Voltage Rating Numeric: 1000 V

Amperage Rating: 20A

Amperage Rating Numeric: 20 A
Interrupt Rating: 20 kAIC Vac/dc
Connection: Ferrule end X ferrule end

Construction Size: 14 x 51 mm
Packaging Type: Standard
Breaking Capacity: 25 A

• Clearing (I2T): 220

Frequency Rating Maximum: 62 HZ
 Frequency Rating Minimum: 45 HZ

• Fuse Shape: cylindrical

• Fuse Indicator: Non Indicating

• Pre Arc (I2T): 25

• Release Characteristic: Other

 Utilization category: aR (accompanied semiconductor protection)



• Voltage Type: AC/DC

Watt Losses: 9With Striker: No

Supporting documents:

Product Catalog

• 1000V 20A S/COND FERRULE 14.5 X 66.7MM

Certifications:

• UL Recognized

Product compliance:

CE Marked

© 2016 Eaton. All rights reserved.