



Analog I/O Modules (Output)

GE offers easy-to-use analog modules for control processes such as flow, temperature and pressure.

	IC695ALG708	IC695ALG728
Product Name	PACSystems RX3i Analog Output, Current/Voltage, 8 Channel	PACSystems RX3i Analog Output with HART Communications, Current/Voltage, 8 Channel
Lifecycle Status	Active	Active
Module Type	Analog Output	Analog Output with HART Communications
Backplane Support	Universal Backplane Only. Uses PCI Bus.	Universal Backplane Only. Uses PCI Bus.
Number of Slots Module Occupies on Backplane	1	1
Diagnostics	High and Low Alarm, Ramp Rate Control Clamping, Overrange and Underrange	High and Low Alarm, Ramp Rate Control, Clamping, Overrange and Underrange
Protection	N/A	N/A
Range	Current: 0 to 20 mA, 4 to 20 mA; Voltage: ±10 V, 0 to 10 V	Current: 0 to 20 mA, 4 to 20 mA; Voltage: ±10 V, 0 to 10 V
HART Support	N/A	-Get HART Device Information (Function 1) Simplified HART Pass-Thru Command (Function 2) -Enterprise HART Pass-Thru Command (Function 3)
Number of Channels	8	8
Channel-to-Channel Isolation	N/A	N/A
Update Rate	8 ms all channels	8 ms all channels and HART enabled channels could add 6 to 8 seconds.
Resolution	10 V: 15.9 bits; 0 to 10 V: 14.9 bits; 0 to 20 mA: 15.9 bits; 4 to 20 mA: 15.6 bits	±10 V: 15.9 bits; 0 to 10 V: 14.9 bits; 0 to 20 mA: 15.9 bits; 4 to 20 mA: 15.6 bits
Accuracy	Accurate to within 0.15% of full scale at 25°C. Accurate to within 0.30% of full scale at 60°C	Accurate to within 0.15% of full scale at 25°C. Accurate to within 0.30% of full scale at 60°C
Maximum Output Load	Current -850ohm max @ Vuser = 20 V; Voltage -2k ohm max load (minimum resistance)	Current -850ohm max @ Vuser = 20 V; Voltage -2k ohm max load (minimum resistance)
Output Load Capacitance	Current: 10uH max.; Voltage: 1uF max.	Current: 10uH max.; Voltage: 1uF max.
External Power Requirement	Voltage Range: 19.2 V to 30 V Current required: 315 mA	Voltage Range: 19.2 V to 30 V Current required: 315 mA
Connector Type	IC694TBB032 or IC694TBS032. Sold Separately	IC694TBB032 or IC694TBS032. Sold Separately.
Internal Power Used	375 mA @3.3 V (internal) 315 mA @24 V (external)	375 mA @3.3 V (internal) 315 mA@24 V (external)