


INSULATING BUSHINGS

Insulating Bushings - Standard Series

G7



Insulating Bushings – Standard Series

These bushings are available in a large selection of sizes from ¼" to 2" in various inside diameter openings. Standard bushings are designed with multiple locks to positively snap in panels ranging from ½" to ⅝" thickness. Standard bushings meet UL and CSA temperature and pull-out tests molded of heat stabilized nylon (UL 94V2).



ITEM NUMBER	PART DIMENSIONS inches(mm)			CHASSIS DIMENSIONS inches(mm)	
	INSIDE DIAMETER A	HEAD DIAMETER B	THICKNESS C	HOLE DIAMETER	MAX THICKNESS
SBE250-2	.125 (3.2)	.312 (8.0)	.312 (8.0)	.250 (6.4)	.062 (1.6)
SBE312-3*	.187 (4.8)	.375 (9.5)	.312 (8.0)	.312 (8.0)	.062 (1.6)
SBE375-3	.187 (4.8)	.468 (11.9)	.406 (10.3)	.375 (9.5)	.125 (3.2)
SBE375-4*	.250 (6.4)	.468 (11.9)	.406 (10.3)	.375 (9.5)	.125 (3.2)
SBE437-4*	.250 (6.4)	.531 (13.5)	.406 (10.3)	.437 (11.1)	.125 (3.2)
SBE437-5*	.312 (8.0)	.531 (13.5)	.406 (10.3)	.437 (11.1)	.125 (3.2)
SBE437-6*	.243 (6.2)	.531 (13.5)	.406 (10.3)	.437 (11.1)	.125 (3.2)
SBE500-4	.250 (6.4)	.578 (14.7)	.406 (10.3)	.500 (12.7)	.125 (3.2)
SBE500-5	.312 (8.0)	.578 (14.7)	.406 (10.3)	.500 (12.7)	.125 (3.2)
SBE500-6	.375 (9.5)	.578 (14.7)	.406 (10.3)	.500 (12.7)	.125 (3.2)
SBE562-5	.312 (8.0)	.656 (16.7)	.406 (10.3)	.562 (14.3)	.125 (3.2)
SBE562-6	.375 (9.5)	.656 (16.7)	.406 (10.3)	.562 (14.3)	.125 (3.2)
SBE562-7	.437 (11.1)	.656 (16.7)	.406 (10.3)	.562 (14.3)	.125 (3.2)
SBE625-4	.250 (6.4)	.718 (18.2)	.406 (10.3)	.625 (15.9)	.125 (3.2)
SBE625-7	.437 (11.1)	.718 (18.2)	.406 (10.3)	.625 (15.9)	.125 (3.2)
SBE625-8*	.500 (12.7)	.718 (18.2)	.406 (10.3)	.625 (15.9)	.125 (3.2)
SBE687-8	.500 (12.7)	.781 (19.8)	.406 (10.3)	.687 (17.4)	.125 (3.2)
SBE687-9	.562 (14.3)	.781 (19.8)	.406 (10.3)	.687 (17.4)	.125 (3.2)
SBE750-6	.375 (9.5)	.843 (21.4)	.406 (10.3)	.750 (19.0)	.125 (3.2)
SBE750-8	.500 (12.7)	.843 (21.4)	.406 (10.3)	.750 (19.0)	.125 (3.2)
SBE750-9	.562 (14.3)	.843 (21.4)	.406 (10.3)	.750 (19.0)	.125 (3.2)
SBE750-10	.625 (15.9)	.843 (21.4)	.406 (10.3)	.750 (19.0)	.125 (3.2)
SBE812-9	.562 (14.3)	.890 (22.6)	.406 (10.3)	.812 (20.6)	.125 (3.2)
SBE812-10	.625 (15.9)	.890 (22.6)	.406 (10.3)	.812 (20.6)	.125 (3.2)
SBE875-6	.375 (9.5)	.953 (24.2)	.453 (11.5)	.875 (20.6)	.125 (3.2)
SBE875-7	.437 (11.1)	.953 (24.2)	.453 (11.5)	.875 (20.6)	.125 (3.2)
SBE875-8	.500 (12.7)	.953 (24.2)	.453 (11.5)	.875 (20.6)	.125 (3.2)
SBE875-9	.562 (14.3)	.953 (24.2)	.453 (11.5)	.875 (20.6)	.125 (3.2)
SBE875-10	.625 (15.9)	.953 (24.2)	.453 (11.5)	.875 (20.6)	.125 (3.2)
SBE875-11	.687 (17.4)	.953 (24.2)	.453 (11.5)	.875 (20.6)	.125 (3.2)
SBE1000-12	.750 (19.0)	1.125 (28.6)	.453 (11.5)	1.000 (25.4)	.125 (3.2)
SBE1093-13	.812 (20.6)	1.218 (30.9)	.453 (11.5)	1.093 (27.8)	.125 (3.2)
SBE1093-14	.875 (22.2)	1.218 (30.9)	.453 (11.5)	1.093 (27.8)	.125 (3.2)
SBE1093-15	.937 (23.8)	1.218 (30.9)	.453 (11.5)	1.093 (27.8)	.125 (3.2)
SBE1187-15	.937 (23.8)	1.312 (33.3)	.453 (11.5)	1.187 (30.2)	.125 (3.2)
SBE1250-15	.937 (23.8)	1.468 (37.3)	.453 (11.5)	1.250 (31.7)	.125 (3.2)
SBE1375-16	1.000 (25.4)	1.468 (37.3)	.453 (11.5)	1.375 (34.9)	.125 (3.2)
SBE1500-17	1.062 (27.0)	1.609 (40.9)	.453 (11.5)	1.500 (38.1)	.125 (3.2)
SBE1500-18	1.125 (28.5)	1.609 (40.9)	.453 (11.5)	1.500 (38.1)	.125 (3.2)
SBE1500-21	1.312 (30.1)	1.609 (40.9)	.453 (11.5)	1.500 (38.1)	.125 (3.2)
SBE1750-22	1.375 (34.9)	1.875 (47.6)	.453 (11.5)	1.750 (44.4)	.125 (3.2)
SBE2000-26	1.625 (41.2)	2.125 (54.0)	.453 (11.5)	2.000 (50.8)	.125 (3.2)

* Add suffix "-WH" for WHITE version. Standard color is BLACK.