

LED Linear Tube

1800 Lumen T8 LED 4000K 48 inch
Type B Double End for Direct Wire - Coated



PRODUCT DESCRIPTION

14 watt EarthBulb direct wire LED linear T8 eliminates the ballast for maximum energy savings. Available in 4000K with 300 degree beam angle. Great light output and perfect for replacement of T8 fluorescent tubes. This linear tube provides 1800 lumens and has a CRI of 82. This lamp is engineered for high lumen maintenance over its 50,000 hour rated. To install, simply remove the existing fluorescent ballast and direct wire the line voltage. Direct wire quickly, no lamp holder modifications necessary, just run the black (load) to the one end and white (neutral) to the other. This product is shatterproof coated. Operates on 120-277V. DLC listed product.

PRODUCT FEATURES

- Easily retrofit T8, 4 foot tubes
- DLC listed product
- Direct wire without modifying lamp holders
- 120/277VAC 50/60Hz, direct wire
- Provides 1800 lumens
- Chipset provides 4000K natural white light with a high color rating of 82
- RoHS Certified
- UL Classified UL 1598C (US & Canada)
- Shatterproof coated for use in food service area

MODEL NUMBER: LT814840BDECT

ORDER CODE: 11183

DLC PRODUCT ID: PLBCJGJROMH8

PACK SIZE: 25



DIMENSIONS:

- Diameter: 1 inch
- Nominal Length: 48 inches

| Electrical | |
|-----------------------------|-----------------------------|
| Watt | 14 |
| Power Factor | > .90 |
| Total Harmonic Distortion | 20% |
| Voltage | 120/277VAC 50/60Hz |
| Base Type | G13 |
| Operating Temperature Range | -20°C to 45°C |
| Light | |
| Initial Lumens | 1800 |
| Lumens per Watt | 128 |
| Color Temperature | 4000K |
| Color Rendering (CRI) | 82 |
| Beam Angle | 300° |
| Agency Approvals | |
| UL/ETL | Yes |
| DLC | Yes |
| RoHS | Yes |
| FCC | Yes, FCC 47 Part 18 CLASS A |
| Product Details | |
| Warranty | 5 years, 10 year limited |
| Mercury Content | 0 |
| Diameter | 1" |
| Nominal Length | 48" |
| Rated Life | 50,000 hours |