



Representative Image

Catalog No. THN3365SS**Description: 400A 3P HD N4X SS 600V NONFUSE****UPC No 783164089394****Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty**

Designed for commercial and industrial applications where safety, high performance and continuity of service are essential. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type HD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism. 60/75 C conductor rating. Full cover interlocks. THN3365S

Descriptors

Category	Heavy Duty
GO Schedule	S1

Specifications

Voltage	600 AC
Amperage	400 A
Poles	3
Wires	3
Fusing	No Fuse
Enclosure	NEMA 4/4X Water/Dust-tight
Options	None
Wire Range (Cu/Al)	(1) 2-600 or (2) 1/0-250
240 Vac, NEC Std, 3-ph	125.0 hp
480 Vac, NEC Std, 3-ph	250.0 hp
600 Vac, NEC Std, 3-ph	350.0 hp
250 Vdc	50.0 hp
GSA Compliance	Yes

Classifications

CSA Certified	Yes
UL Listed	Yes

Dimensions

Height	48.0 in
Depth	8.4 in
Width	24.6 in
Weight	239.0 lb


by ABB

Publications

Title	Publication No.	Publication Type
Stainless Steel Safety Switches Sealed Tight - Latch it! New over center latch system requires no tools to open the switch. Designed for commercial and industrial applications in corrosive environments where safety, high performance and continuity of service are essential. DET-842 Spec-Setter Safety Switches	15QC920001L0201	Brochures
845 600A - Safety Switches	15QC920001B0201	Brochures
1 page outline drawing in .pdf format.	10103091-SH119	Drawings-Outline and Dimensional

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.