


MEDIUM BASE


H22

MEDIUM BASE HID 4KV PULSE RATED LAMPHOLDERS

IS267S-1 Medium Base 4KV Pulse Rated Lampholder with 6/32" Mounting Screws

		E - 26	1" BASE DIAMETER	<ul style="list-style-type: none"> - White glazed porcelain body - Copper alloy nickel-plated screw shell - Copper alloy nickel-plated centre contact - Standard leads are 18 AWG, SEW-2 (SF2) 600V 200°C, 12" long, or specify desired wire and length 	<ul style="list-style-type: none"> - Supplied with insulating fibre - Supplied with two #6-32 mounting screws on 27/32" centres - Die cast caps are available - 660W, 600V - UL Listed
					

IS267S-2 Medium Base 4KV Pulse Rated Lampholder with 6/32" Female Bushings

		E - 26	1" BASE DIAMETER	<ul style="list-style-type: none"> - White glazed porcelain body - Copper alloy nickel-plated screw shell - Copper alloy nickel-plated centre contact - With screw terminals - Supplied with insulating fibre 	<ul style="list-style-type: none"> - Supplied with two captive #6-32 threaded bushings on 27/32" centres - Die cast caps are available - 660W, 600V - UL Listed
					

IS267-EP-1 4KV Pulse Rated-Medium Base with Mounting Screws

		E - 26	1" BASE DIAMETER	<ul style="list-style-type: none"> - For use in applications with the GE MXR 32W Metal Halide lamp. - Copper alloy nickel-plated screw shell. - Leaf spring supported nickel plated center contact. - White glazed porcelain body. - Special extended body design to conform 	<ul style="list-style-type: none"> - with UL requirements for the live screwshell - Standard leads are 18 gauge SF-200C leads 12" long - Available with lamp grip screwshell. - Available with screwshell reinforcing washers - 660W, 600V - cULus
				