



Representative Image

**Catalog No. TG4322****Description: 60A 3P GD N1 240V FUSIBLE SWITCH****UPC No 783164008654****Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > General Duty**

Designed for residential and light commercial applications where duty is not severe. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type GD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism (30-200 amp). 60/75 C conductor rating. TG4322

**Descriptors**

Category

General Duty

**Specifications**

Amperage	60 A
Poles	3
Wires	4
Fusing	Fusible
Enclosure	NEMA 1 (Indoor)
Wire Range (Cu/Al)	12-2
240 Vac, NEC Std, 1-ph	3
240 Vac, NEC Std, 3-ph	7.5
240 Vac, Time Delay, 1-ph	10
240 Vac, Time Delay, 3-ph	15
250 Vdc	10
GSA Compliance	Yes

**Classifications**

CSA Certified	Yes
UL Listed	Yes

**Dimensions**

Height	13.8
Depth	4
Width	8.4
Weight	10

## Publications

Title	Publication No.	Publication Type
<a href="#">General Duty Safety Switches: 30-600 Amp, 240 Vac</a> 1 page. For residential and light commercial applications.	DEE-576	Brochures
<a href="#">60A - Safety Switches</a> 1 page outline drawing in .pdf format.	10103091-SH104	Drawings-Outline and Dimensional

**Additional Documentation:** Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.