



### Catalog No. TGN3321

Description: 30A 3P GD N1 240V NONFUSE SWITCH

UPC No 783164008784

Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > General Duty

Designed for residential and light commercial applications where duty is not severe. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type GD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism (30-200 amp). 60/75 C conductor rating. TGN3321



Representative Image

#### Descriptors

Category	General Duty
----------	--------------

#### Specifications

Amperage	30 A
Poles	3
Wires	3
Fusing	No Fuse
Enclosure	NEMA 1 (Indoor)
Wire Range (Cu/Al)	12-8 AL 14-8 CU
240 Vac, NEC Std, 1-ph	3
240 Vac, NEC Std, 3-ph	7.5
250 Vdc	5
GSA Compliance	Yes

#### Classifications

CSA Certified	Yes
UL Listed	Yes

#### Dimensions

Height	10.3
Depth	3.3
Width	6.4
Weight	5



## Publications

Title	Publication No.	Publication Type
<a href="#">General Duty Safety Switches: 30-600 Amp, 240 Vac</a>	DEE-576	Brochures
1 page. For residential and light commercial applications.		
<a href="#">60A - Safety Switches</a>	10103091-SH104	Drawings-Outline and Dimensional
1 page outline drawing in .pdf format.		

**Additional Documentation:** Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.