



Catalog No. TGN3323

Description: 100A 3P GD N1 240V NONFUSE SW

UPC No 783164008821

Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > General Duty

Designed for residential and light commercial applications where duty is not severe. Listed to UL standard 98 enclosed and dead front switches. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type GD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism (30-200 amp). 60/75 C conductor rating. TGN3323



Representative Image

Descriptors

Category	General Duty
----------	--------------

Specifications

Amperage	100 A
Poles	3
Wires	3
Fusing	No Fuse
Enclosure	NEMA 1 (Indoor)
Wire Range (Cu/Al)	10-1/0
240 Vac, NEC Std, 1-ph	15
240 Vac, NEC Std, 3-ph	30
250 Vdc	20
GSA Compliance	Yes

Classifications

CSA Certified	Yes
UL Listed	Yes

Dimensions

Height	21.3
Depth	4.9
Width	9.4
Weight	16



Publications

Title	Publication No.	Publication Type
200A - Safety Switches 1 page outline drawing in .pdf format.	10103091-SH108	Drawings-Outline and Dimensional
General Duty Safety Switches: 30-600 Amp, 240 Vac 1 page. For residential and light commercial applications.	DEE-576	Brochures

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.