



Representative Image

Catalog No. TH2221SS

Description: 30A 2P HD N4X SS 240V FUSIBLE SW

UPC No 783164092554

Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty

Designed for commercial and industrial applications where safety, high performance and continuity of service are essential. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type HD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism. 60/75 C conductor rating. Full cover interlocks. TH2221SS

Descriptors

Category	Heavy Duty
GO Schedule	S1

Specifications

Voltage	240 AC
Amperage	30 A
Poles	2
Wires	2
Fusing	Fusible
Enclosure	NEMA 4/4X Water/Dust-tight
Options	None
Wire Range (Cu/Al)	14-8 CU;12-8 AL
240 Vac, NEC Std, 1-ph	1.5 hp
240 Vac, Time Delay, 1-ph	3.0 hp
250 Vdc	5.0 hp
GSA Compliance	Yes

Classifications

CSA Certified	Yes
UL Listed	Yes

Dimensions

Height	11.3 in
Depth	5.4 in
Width	7.4 in
Weight	12.0 lb

by ABB

Publications

Title	Publication No.	Publication Type
Stainless Steel Safety Switches Sealed Tight - Latch it! New over center latch system requires no tools to open the switch. Designed for commercial and industrial applications in corrosive environments where safety, high performance and continuity of service are essential. DET-842	1SQC920001L0201	Brochures
Spec-Setter Safety Switches 845	1SQC920001B0201	Brochures
60A (incl. 316 Stainless) - Safety Switches 1 page outline drawing in .pdf format.	10103091SH109	Drawings-Outline and Dimensional

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.