



Representative Image

Catalog No. THQD32225WL**Description: THQD 3P 225A 22KA LINE/LOAD LUGS****UPC No 783164088014****Home > Circuit Breakers > Miniature Circuit Breakers > Q-Line Miniature Circuit Breakers**

The TQD Line of devices include thermal magnetic molded case circuit breakers and molded case switches. The devices are complete with Cu/Al line and load lugs. 25WL Amps 225 A

Descriptors

Category	Q-Line Miniature Circuit Breakers
Product Line	Thermal Magnetic
GO Schedule	EF

Specifications

Trip Style	Non-Interchangeable
Frame Type	Q-Line
Amperage	225 A
System Voltage	120 Vac 120/240 Vac 240 Vac
Poles	3
Trip Function	LI
Continuous Current Rated	Standard
120 Vac Interrupting Rating	22 KAIC
120/240 Vac Interrupting Rating	22 KAIC
240 Vac Interrupting Rating	22 KAIC
Lugs	TCAL25
Suitable for Reverse Feed	Yes
Long Time	Fixed
Instantaneous	Fixed
Protective Relays	No
Current Metering	No
Special Markings	HACR
GSA Compliance	No

Classifications

UL File #	E11592
-----------	--------

Publications

Title	Publication No.	Publication Type
TQD / THQD MCCB, 3- Pole 100-225 Ampere, Drawing 1 page, Fully Dimensioned Layout Drawing in .dxf format	455C765-SH1-DXF	Drawings-Outline and Dimensional
TQD / THQD MCCB, 3- Pole 100-225 Ampere, Drawing 1 page, Fully Dimensioned Layout Drawing in .pdf format	455C765-SH1	Drawings-Outline and Dimensional
TQD / THQD MCCB, 2- and 3- Pole 100-225 Ampere, Drawing 1 page, Non-dimensioned full scale layout drawing in .dxf format	TQD225 2-3P-DXF	Drawings-Outline and Dimensional

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.