



Catalog No. GPS1BHAL

Description: MMS HIGH BK 9 - 13 AMPS

UPC No 4538915012444

Home > Starters > IEC > Manual Motor Starter - SURION

- MANUAL MOTOR STARTER T+M PROT. GPS1 9-13A HIGH BREAKING
- Pack-5



Representative Image

Descriptors

Category	Manual Motor Starter - SURION
GO Schedule	CC

Specifications

Rated Current	13.0 A
Capacity	GPS1BH - High breaking capacity
Instantaneous short-circuit release (A)	169
Rated power 3 phase motors at 220/230Vac Pn (hp)	3
Rated power 3 phase motors at 400Vac Pn (hp)	3
Rated power 3 phase motors at 440Vac Pn (hp)	7 1/2
Rated power 3 phase motors at 500/525Vac Pn (hp)	10
Rated service short-circuit breaking cap 220/230V Ics kA	100
Rated service short-circuit breaking cap 400V Ics kA	50
Rated service short-circuit breaking cap 440V Ics kA	10
Rated service short-circuit breaking cap 500/525V Ics kA	32
Rated service short-circuit breaking cap 600V Ics kA	5
Rated service short-circuit breaking cap 690V Ics kA	5
Rated ultimate short-circuit breaking cap 220/230V Icu kA	100
Rated ultimate short-circuit breaking cap 400V Icu kA	25
Rated ultimate short-circuit breaking cap 440V Icu kA	25
Rated ultimate short-circuit breaking cap 500/525V Icu kA	42
Rated ultimate short-circuit breaking cap 600V Icu kA	6
Rated ultimate short-circuit breaking cap 690V Icu kA	6
Series	Surion - GPS1B - Thermal and magnetic protection (Ie max 32A)
Thermal current setting range (A)	9 - 13 A
Trip class IEC 60947-4-1	Class 10
Single Phase Horsepower @ 115V	1/2
Single Phase Horsepower @ 230V	2
FLA Adjustment Range	9 - 13 A
Max. Fuse Size (A)	50
Max Circuit Breaker Size (A)	50
Max. Fuse or Circuit Breaker Size - Group Installation (A)	500

by ABB

Specifications

Rated Breaking Capacity @ 277Y/480V - Combination Starter (kA)	50
Minimum Contactor Size	CL00
GSA Compliance	No

Dimensions

Weight	0.79 lb
Width	45.0 mm